

## 1. Product and Company Identification

**Product Code:** 0238A  
**Product Name:** 0238A  
**Company Name:** Appli-Tec, Inc  
 7 Industrial Way Unit 1  
 Salem, NH 03079  
**Phone Number:** (603)685-0500

**Web site address:** www.appli-tec.com

**Emergency Contact:** Contact medical emergency services  
**Information:** Call Chemtrec for Transport Info. (800)424-9300

**Intended Use:** Resin for two part adhesive

## 2. Hazards Identification

**Skin Corrosion/Irritation, Category 2**  
**Serious Eye Damage/Eye Irritation, Category 2A**  
**Skin Sensitization, Category 1**



**GHS Signal Word:** Warning

**GHS Hazard Phrases:** H315 - Causes skin irritation.  
 H319 - Causes serious eye irritation.  
 H317 - May cause an allergic skin reaction.

**GHS Precaution Phrases:** P264 - Wash hands thoroughly after handling.  
 P280 - Wear protective gloves/eye protection/face protection.  
 P261 - Avoid breathing vapors, mist, or spray.  
 P272 - Contaminated work clothing should not be allowed out of the workplace.

**GHS Response Phrases:** P302+352 - IF ON SKIN: Wash with plenty of soap and water.  
 P362 - Take off contaminated clothing.  
 P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P337+313 - If eye irritation persists, get medical advice/attention.  
 P333+313 - If skin irritation or rash occurs, seek medical advice/attention.

**GHS Storage and Disposal Phrases:** P501 - Dispose of contents/container according to national and local regulations.

**OSHA Regulatory Status:** This material is classified as hazardous under OSHA regulations.

**Potential Health Effects (Acute and Chronic):**

**Inhalation:** May cause respiratory tract irritation. May cause severe allergic respiratory reaction.

**Skin Contact:** May cause skin irritation. May cause allergic skin reaction.

**Eye Contact:** May cause eye irritation.

**Ingestion:** Ingestion of large amounts may cause gastrointestinal irritation.

**Additional Information** No data available.

### 3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
12001-26-2	Mica-group minerals	50.0 -60.0 %
25068-38-6	Bisphenol-a based epoxy resin	40.0 -50.0 %
122-60-1	Phenyl glycidyl ether	1.0 -5.0 %
14808-60-7	Quartz	0.1 -1.0 %
1333-86-4	Carbon black	0.1 -1.0 %

**Additional Information** Exact percentages have been withheld as a trade secret.

### 4. First Aid Measures

**Emergency and First Aid Procedures:**

- In Case of Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.
- In Case of Skin Contact:** Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash contaminated clothing before reuse.
- In Case of Eye Contact:** Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention/advice.
- In Case of Ingestion:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical advice/attention.

### 5. Fire Fighting Measures

- Flash Pt:** > 93.00 C
- Explosive Limits:** LEL: N.D. UEL: N.D.
- Autoignition Pt:** No data.
- Suitable Extinguishing Media:** Use water spray, dry chemical, carbon dioxide, or appropriate foam.
- Fire Fighting Instructions:** As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear.
- Flammable Properties and Hazards:** No data available.
- Hazardous Combustion Products:** No data available.

### 6. Accidental Release Measures

- Steps To Be Taken In Case Material Is Released Or Spilled:** Ensure adequate ventilation. Isolate area and deny entry. Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Use proper personal protective equipment as indicated in Section 8. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

### 7. Handling and Storage

- Precautions To Be Taken in Handling:** Use with adequate ventilation. Avoid contact with eyes, skin, and clothing. Do not breathe dust, mist, or vapor. Wash thoroughly after handling.
- Precautions To Be Taken in Storing:** Store in cool/well-ventilated place. Keep away from heat, sparks and flame. Keep container tightly closed.

## 8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
12001-26-2	Mica-group minerals	PEL: 706 ppm/20 mppcf	TLV: 3 mg/m3 (R)	No data.
25068-38-6	Bisphenol-a based epoxy resin	No data.	No data.	No data.
122-60-1	Phenyl glycidyl ether	PEL: 10 ppm	TLV: 0.1 ppm	No data.
14808-60-7	Quartz	PEL: 8825 ppm/(%SiO2+5)	TLV: 0.05 mg/m3 (R)	No data.
1333-86-4	Carbon black	PEL: 3.5 mg/m3	TLV: 3 mg/m3 (IHL)	No data.

<b>Respiratory Equipment (Specify Type):</b>	Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
<b>Eye Protection:</b>	Safety glasses.
<b>Protective Gloves:</b>	Wear appropriate protective gloves to prevent skin exposure.
<b>Other Protective Clothing:</b>	Wear appropriate protective clothing to prevent skin exposure.
<b>Engineering Controls (Ventilation etc.):</b>	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.
<b>Work/Hygienic/Maintenance Practices:</b>	Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling.

## 9. Physical and Chemical Properties

<b>Physical States:</b>	<input type="checkbox"/> Gas <input checked="" type="checkbox"/> Liquid <input type="checkbox"/> Solid
<b>Appearance and Odor:</b>	Appearance: Black. Liquid. Odor: Odorless.
<b>Melting Point:</b>	No data.
<b>Boiling Point:</b>	No data.
<b>Flash Pt:</b>	> 93.00 C
<b>Evaporation Rate:</b>	No data.
<b>Flammability (solid, gas):</b>	No data available.
<b>Explosive Limits:</b>	LEL: N.D.      UEL: N.D.
<b>Vapor Pressure (vs. Air or mm Hg):</b>	No data.
<b>Vapor Density (vs. Air = 1):</b>	No data.
<b>Specific Gravity (Water = 1):</b>	~1.6
<b>Solubility in Water:</b>	No data.
<b>Percent Volatile:</b>	No data.
<b>Autoignition Pt:</b>	No data.

## 10. Stability and Reactivity

<b>Stability:</b>	Unstable <input type="checkbox"/> Stable <input checked="" type="checkbox"/>
<b>Conditions To Avoid - Instability:</b>	High temperatures, flames and sparks. Incompatible materials.
<b>Incompatibility - Materials To Avoid:</b>	Strong oxidizing agents, Strong acids, Strong bases, alliphatic amines.
<b>Hazardous Decomposition or Byproducts:</b>	oxides of carbon. Aldehydes, Acids. Irritating organic vapors.
<b>Possibility of Hazardous Reactions:</b>	Will occur <input type="checkbox"/> Will not occur <input checked="" type="checkbox"/>
<b>Conditions To Avoid -</b>	No data available.

**Hazardous Reactions:**

**11. Toxicological Information**

**Toxicological Information:** No data available.  
**Irritation or Corrosion:** Skin and eye irritant.  
**Sensitization:** Skin sensitization.  
**Carcinogenicity/Other Information:** Contains material which may cause cancer, based on animal data. Risk depends on level and duration of exposure.

**12. Ecological Information**

No data available.

**13. Disposal Considerations**

**Waste Disposal Method:** Observe all federal, state, and local environmental regulations.

**14. Transport Information**

**LAND TRANSPORT (US DOT):**

**DOT Proper Shipping Name:** Not Regulated.  
**DOT Hazard Class:**  
**UN/NA Number:**

**MARINE TRANSPORT (IMDG/IMO):**

**IMDG/IMO Shipping Name:** Environmentally Hazardous Substance, liquid, n.o.s. (Liquid Epoxy Resin).  
**UN Number:** 3082 **Packing Group:** III  
**Hazard Class:** 9 - CLASS 9 **IMDG MFAG Number:**

**IMDG EMS Page:**

**AIR TRANSPORT (ICAO/IATA):**

**ICAO/IATA Shipping Name:** Environmentally Hazardous Substance, liquid, n.o.s. (Liquid Epoxy Resin).  
**UN Number:** 3082 **Packing Group:** III  
**Hazard Class:** 9 - CLASS 9

**15. Regulatory Information**

**EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists**

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
12001-26-2	Mica-group minerals	No	No	No
25068-38-6	Bisphenol-a based epoxy resin	No	No	No
122-60-1	Phenyl glycidyl ether	No	No	No
14808-60-7	Quartz	No	No	No
1333-86-4	Carbon black	No	No	No

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
12001-26-2	Mica-group minerals	TSCA: Yes - Inventory
25068-38-6	Bisphenol-a based epoxy resin	TSCA: Yes - Inventory
122-60-1	Phenyl glycidyl ether	TSCA: Yes - Inventory, 4 Test, 8A
14808-60-7	Quartz	TSCA: Yes - Inventory
1333-86-4	Carbon black	TSCA: Yes - Inventory

## 16. Other Information

**Revision Date:** 06/15/2017

**Additional Information About This Product:** No data available.

**Company Policy or Disclaimer:** The information on this data sheet represents our current and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or the applicable technical bulletin, or which involves using the product in combination with any other product or any other process is the responsibility of the user.