

## 1. Product and Company Identification

**Product Code:** 0421  
**Product Name:** 0421  
**Company Name:** Appli-Tec, Inc  
 7 Industrial Way Unit 1  
 Salem, NH 03079  
**Phone Number:** (603)685-0500  
**Web site address:** www.appli-tec.com  
**Emergency Contact:** Contact medical emergency services  
**Information:** Call Chemtrec for Transport Info. (800)424-9300  
**Intended Use:** Adhesive

## 2. Hazards Identification

**Skin Corrosion/Irritation, Category 1C**  
**Serious Eye Damage/Eye Irritation, Category 1**  
**Skin Sensitization, Category 1**



**GHS Signal Word:** Danger  
**GHS Hazard Phrases:** H314 - Causes severe skin burns and eye damage.  
 H317 - May cause an allergic skin reaction.  
**GHS Precaution Phrases:** P260 - Do not breathe vapors, mist, or spray.  
 P264 - Wash hands thoroughly after handling.  
 P272 - Contaminated work clothing should not be allowed out of the workplace.  
 P280 - Wear protective gloves/eye protection/face protection.  
**GHS Response Phrases:** P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
 P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P310 - Immediately call a POISON CENTER or doctor/physician.  
 P333+313 - If skin irritation or rash occurs, seek medical advice/attention.  
 P363 - Wash contaminated clothing before reuse.  
**GHS Storage and Disposal Phrases:** P405 - Store locked up.  
 P501 - Dispose of contents/container according to national and local regulations.  
**OSHA Regulatory Status:** This material is classified as hazardous under OSHA regulations.  
**Potential Health Effects (Acute and Chronic):**  
**Inhalation:** May be harmful if inhaled.  
**Skin Contact:** Causes skin burns. May cause allergic skin reaction.  
**Eye Contact:** Causes eye burns. Causes serious eye damage.  
**Ingestion:** This material may be harmful or fatal if swallowed.  
**Additional Information** No data available.

### 3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
NA	Proprietary epoxy resin	30.5 -50.0 %
1317-65-3	Limestone	20.0 -45.0 %
NA	Proprietary Amine Aduct	15.0 -30.0 %
112945-52-5	Silica, amorphous treated	0.5 -2.5 %
112-24-3	1,2-Ethanediamine, N,N'-Bis(2-aminoethyl)-	0.5 -2.5 %
7631-86-9	Silica	0.5 -2.5 %
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	0.5 -2.5 %
NA	Proprietary Substituted aminophenol	0.05 -0.5 %

**Additional Information** Exact percentages have been withheld as a trade secret.

### 4. First Aid Measures

**Emergency and First Aid Procedures:**

- In Case of Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.
- In Case of Skin Contact:** Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash contaminated clothing before reuse.
- In Case of Eye Contact:** Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention/advice.
- In Case of Ingestion:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical advice/attention.
- Signs and Symptoms Of Exposure:** Prolonged inhalation of crystalline silica may result in silicosis, a disabling pulmonary fibrosis characterized by fibrotic changes and miliary nodules in the lungs, a dry cough, shortness of breath, emphysema, decreased chest expansion, and increased susceptibility to tuberculosis. In advanced stages, loss of appetite, pleuritic pain, and total incapacity to work. Advanced silicosis may result in death due to cardiac failure or destruction of lung tissue. Crystalline silica is classified as group 1 "known to be carcinogenic to humans" by IARC and "sufficient evidence" of carcinogenicity by the NTP. The chronic health risks are associated with respirable particles of 3-4 um over protracted periods of time. Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin. Inhalation may result in spasm, inflammation and edema of the larynx and bronchi, chemical pneumonitis, and pulmonary edema. Symptoms of exposure may include burning sensation, coughing, wheezing, laryngitis, shortness of breath, headache, nausea, and vomiting. To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.
- Note to Physician:** Treat symptomatically and supportively.

## 5. Fire Fighting Measures

**Flash Pt:** 93.00 C

**Explosive Limits:** LEL: No data. UEL: No data.

**Autoignition Pt:** No data.

**Suitable Extinguishing Media:** Use water spray, dry chemical, carbon dioxide, or appropriate foam.

**Fire Fighting Instructions:** As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear.

**Flammable Properties and Hazards:** No data available.

**Hazardous Combustion Products:** No data available.

## 6. Accidental Release Measures

**Steps To Be Taken In Case Material Is Released Or Spilled:** Ensure adequate ventilation. Isolate area and deny entry. Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Use proper personal protective equipment as indicated in Section 8. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

## 7. Handling and Storage

**Precautions To Be Taken in Handling:** Avoid breathing dust, mist, or vapor. Avoid contact with skin and eyes. Wash thoroughly after handling.

**Precautions To Be Taken in Storing:** Store at <= -40deg.C.

## 8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
NA	Proprietary epoxy resin	No data.	No data.	No data.
1317-65-3	Limestone	PEL: 15 (dust); 5 (resp.) mg/m3	No data.	No data.
NA	Proprietary Amine Adduct	No data.	No data.	No data.
112945-52-5	Silica, amorphous treated	No data.	No data.	No data.
112-24-3	1,2-Ethanediamine, N,N'-Bis(2-aminoethyl)-	No data.	No data.	No data.
7631-86-9	Silica	No data.	No data.	No data.
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	No data.	No data.	No data.
NA	Proprietary Substituted aminophenol	No data.	No data.	No data.

**Respiratory Equipment (Specify Type):** Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Eye Protection:** Safety glasses.

**Protective Gloves:** Wear appropriate protective gloves to prevent skin exposure.

**Other Protective Clothing:** Wear appropriate protective clothing to prevent skin exposure.

**Engineering Controls (Ventilation etc.):** Use adequate ventilation to keep airborne concentrations low. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

**Work/Hygienic/Maintenance Practices:** Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

**9. Physical and Chemical Properties**

**Physical States:** [ ] Gas [ X ] Liquid [ ] Solid  
**Appearance and Odor:** Appearance: Light. green. Paste.  
 Odor: weak odor.  
**Melting Point:** No data.  
**Boiling Point:** No data.  
**Flash Pt:** 93.00 C  
**Evaporation Rate:** No data.  
**Flammability (solid, gas):** No data available.  
**Explosive Limits:** LEL: No data. UEL: No data.  
**Vapor Pressure (vs. Air or mm Hg):** No data.  
**Vapor Density (vs. Air = 1):** No data.  
**Specific Gravity (Water = 1):** No data.  
**Solubility in Water:** No data.  
**Percent Volatile:** No data.  
**Autoignition Pt:** No data.

**10. Stability and Reactivity**

**Stability:** Unstable [ X ] Stable [ ]  
**Conditions To Avoid - Instability:** Product will cure at ambient temperatures. Keep in cold storage until ready to use.  
**Incompatibility - Materials To Avoid:** Water, Strong bases, Alcohols, Oxidizing materials.  
**Hazardous Decomposition or Byproducts:** Carbon oxides, Nitrogen oxides.  
**Possibility of Hazardous Reactions:** Will occur [ ] Will not occur [ X ]  
**Conditions To Avoid - Hazardous Reactions:** No data available.

**11. Toxicological Information**

**Toxicological Information:** No data available.  
**Irritation or Corrosion:** Serious eye damage/irritation. Skin corrosion/irritation.  
**Sensitization:** Skin sensitization.

**12. Ecological Information**

No data available.

**13. Disposal Considerations**

**Waste Disposal Method:** Observe all federal, state, and local environmental regulations.

**14. Transport Information**

**LAND TRANSPORT (US DOT):**

**DOT Proper Shipping Name:** Not Regulated.  
**DOT Hazard Class:**  
**UN/NA Number:**

**MARINE TRANSPORT (IMDG/IMO):**

**IMDG/IMO Shipping Name:** Environmentally Hazardous Substance, Liquid, n.o.s. (dimer fatty acid(C18)poly amido amine resin)

**UN Number:** 3082 **Packing Group:** III  
**Hazard Class:** 9 - CLASS 9

**IMDG MFAG Number:**

**IMDG EMS Page:**

**AIR TRANSPORT (ICAO/IATA):**

**ICAO/IATA Shipping Name:** Environmentally Hazardous Substance, Liquid, n.o.s. (dimer fatty acid(C18)poly amido amine resin)

**UN Number:** 3082 **Packing Group:** III  
**Hazard Class:** 9 - CLASS 9

**15. Regulatory Information**

**EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists**

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
NA	Proprietary epoxy resin	No	No	No
1317-65-3	Limestone	No	No	No
NA	Proprietary Amine Aduct	No	No	No
112945-52-5	Silica, amorphous treated	No	No	No
112-24-3	1,2-Ethanediamine, N,N'-Bis(2-aminoethyl)-	No	No	No
7631-86-9	Silica	No	No	No
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	No	No	No
NA	Proprietary Substituted aminophenol	No	No	No

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
NA	Proprietary epoxy resin	TSCA: Yes - Inventory
1317-65-3	Limestone	TSCA: Yes - Inventory
NA	Proprietary Amine Aduct	TSCA: Yes - Inventory
112945-52-5	Silica, amorphous treated	TSCA: Yes - Inventory
112-24-3	1,2-Ethanediamine, N,N'-Bis(2-aminoethyl)-	TSCA: Yes - Inventory

7631-86-9	Silica	TSCA: Yes - Inventory
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	TSCA: Yes - Inventory
NA	Proprietary Substituted aminophenol	TSCA: No

**16. Other Information**

<b>Revision Date:</b>	07/19/2016
<b>Additional Information About This Product:</b>	No data available.
<b>Company Policy or Disclaimer:</b>	The information on this data sheet represents our current and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or the applicable technical bulletin, or which involves using the product in combination with any other product or any other process is the responsibility of the user.