

Page: 1 of 6

Revision: 06/13/2017 Supersedes Revision: 01/31/2017

1. Product and Company Identification

Product Code: 0870 Product Name: 0870

Company Name: Appli-Tec, Inc Phone Number: 7 Industrial Way Unit 1 (603)685-0500

7 Industrial Way Unit 1 Salem, NH 03079

Web site address: www.appli-tec.com

Emergency Contact: Contact medical emergency services

Information: Call Chemtrec for Transport Info. (800)424-9300

Intended Use: Adhesive

2. Hazards Identification

Acute Toxicity: Oral, Category 4
Skin Corrosion/Irritation, Category 1A
Serious Eye Damage/Eye Irritation, Category 1

Skin Sensitization, Category 1





GHS Signal Word: Danger

GHS Hazard Phrases: H302 - Harmful if swallowed.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

GHS Precaution Phrases: P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P260 - Do not breathe vapors, mist, or spray.

P280 - Wear protective gloves/eye protection/face protection.

P272 - Contaminated work clothing should not be allowed out of the workplace.

GHS Response Phrases: P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all

contaminated clothing. Rinse skin with water/shower. P363 - Wash contaminated clothing before reuse.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing.

P310 - Immediately call a poison control center doctor.

P333+313 - If skin irritation or rash occurs, seek medical advice/attention.

GHS Storage and Disposal P501 - Dispose of contents/container according to national and local regulations.

Phrases: P405 - Store locked up.

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.



Page: 2 of 6

Revision: 06/13/2017 Supersedes Revision: 01/31/2017

Potential Health Effects (Acute and Chronic):

Inhalation: Harmful if inhaled.

Skin Contact: Causes skin burns. May cause allergic skin reaction. **Eye Contact:** Causes eye burns. Causes serious eye damage.

Ingestion:Harmful if swallowed.Additional InformationNo data available.

3. Composition/Information on Ingredients

CAS#	Hazardous Components (Chemical Name)	Concentration
1344-28-1	Aluminum oxide	65.0 -75.0 %
NA	Proprietary epoxy resin	15.0 -30.0 %
112945-52-5	Silica, amorphous treated	0.5 -5.0 %
2426-08-6	Oxirane, (Butoxymethyl)-	0.5 -5.0 %
9046-10-0	*Poly(oxy(methyl-1,2-ethanediyl)	1.0 -5.0 %
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	1.0 -5.0 %
1333-86-4	Carbon black	0.0 -1.0 %

Additional Information Exact percentages have been withheld as a trade secret.

4. First Aid Measures

Emergency and First Aid

Procedures:

In Case of Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get immediate medical attention.

In Case of Skin Contact: Remove contaminated clothing. Wash skin with soap and water. Get medical

attention. Wash contaminated clothing before reuse.

In Case of Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally

lifting the upper and lower eyelids. Get immediate medical advice/attention.

In Case of Ingestion: Do NOT induce vomiting. Never give anything by mouth to an unconscious

person. Get medical advice/attention.

5. Fire Fighting Measures

Flash Pt: > 93.33 C

Explosive Limits: LEL: No data. UEL: No data.

Autoignition Pt: No data.

Suitable Extinguishing

Media:

Use water spray, dry chemical, carbon dioxide, or appropriate foam.

Fire Fighting Instructions: As in any fire, wear a self-contained breathing apparatus in pressure-demand,

MSHA/NIOSH (approved or equivalent), and full protective gear.

Flammable Properties and No data available.

Hazards:

Hazardous Combustion No

No data available.

Products:



Page: 3 of 6

Revision: 06/13/2017 Supersedes Revision: 01/31/2017

6. Accidental Release Measures

Material Is Released Or Spilled:

Steps To Be Taken In Case Ensure adequate ventilation. Isolate area and deny entry. Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Use proper personal protective equipment as indicated in Section 8. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

7. Handling and Storage

Precautions To Be Taken

Precautions To Be Taken

Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Use

only in a well ventilated area. in Handling:

Store at <= -40deg.C.

in Storing:

8. Exposure Controls/Personal Protection

CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
1344-28-1	Aluminum oxide	PEL: 15 (dust); 5 (resp.) mg/m3	TLV: 10 mg/m3 (E)	No data.
NA	Proprietary epoxy resin	No data.	No data.	No data.
112945-52-5	Silica, amorphous treated	No data.	No data.	No data.
2426-08-6	Oxirane, (Butoxymethyl)-	PEL: 50 ppm	TLV: 3 ppm	No data.
9046-10-0	*Poly(oxy(methyl-1,2-ethanediyl)	No data.	No data.	No data.
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamin e)	No data.	No data.	No data.
1333-86-4	Carbon black	PEL: 3.5 mg/m3	TLV: 3 mg/m3 (IHL)	No data.

Respiratory Equipment

Use a NIOSH/MSHA or European Standard EN 149 approved respirator if

(Specify Type):

exposure limits are exceeded or if irritation or other symptoms are experienced.

Eye Protection: Safety glasses.

Protective Gloves: Wear appropriate protective gloves to prevent skin exposure. Other Protective Clothing: Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation etc.):

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use process enclosure, local exhaust ventilation, or

other engineering controls to control airborne levels below recommended

exposure limits.

Work/Hygienic/Maintenanc Handle in accordance with good industrial hygiene and safety practice. Wash

e Practices:

thoroughly after handling.

Page: 4 of 6

Revision: 06/13/2017 Supersedes Revision: 01/31/2017

9. Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: Appearance: Black. Paste.

Odor: amine-like.

Melting Point:No data.Boiling Point:No data.Flash Pt:> 93.33 CEvaporation Rate:No data.

Flammability (solid, gas): No data available.

Explosive Limits: LEL: No data. UEL: No data.

Vapor Pressure (vs. Air or No data.

mm Hg):

Vapor Density (vs. Air = 1): No data. Specific Gravity (Water = ~2.2

1):

Solubility in Water: No data.

Percent Volatile: No data.

Autoignition Pt: No data.

10. Stability and Reactivity

Stability: Unstable [X] Stable []

Conditions To Avoid - Product will cure at ambient temperatures. Keep in cold storage until ready to

Instability: use.

Incompatibility - Materials Strong oxidizing agents, Strong acids.

To Avoid:

Hazardous Decomposition Carbon oxides, Nitrogen oxides.

or Byproducts:

Possibility of Hazardous Will occur [] Will not occur [X]

Reactions:

Conditions To Avoid - No data available.

Hazardous Reactions:

11. Toxicological Information

Toxicological Information: No data available.

Irritation or Corrosion: Serious eye damage/irritation. Skin corrosion/irritation.

Sensitization: Skin sensitization.

12. Ecological Information

No data available.

13. Disposal Considerations

Waste Disposal Method: Observe all federal, state, and local environmental regulations.

14. Transport Information



Page: 5 of 6

Revision: 06/13/2017 Supersedes Revision: 01/31/2017

LAND TRANSPORT (US DOT):

DOT Proper Shipping Polyamines, liquid, corrosive, n.o.s. (Polyoxy propylene diamine,

Name: 3,3'-oxybis(ethyleneoxy)bis(propylamine))

DOT Hazard Class: 8 CORROSIVE

UN/NA Number: UN2735 Packing Group: II



MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Polyamines, liquid, corrosive, n.o.s.

Polyoxypropylenediamine,3,3'-oxybis(ethyleneoxy)bis(propylamine))

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Polyamines, liquid, corrosive, n.o.s.

Name: (Polyoxypropylenediamine,3,3'-oxybis(ethlyeneoxy)bis(propylamine))

15. Regulatory Information

EPA SARA (Superfund	d Amendments and Reauthorization Act of 1986) Lists	3
----------------------------	---	---

CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
1344-28-1	Aluminum oxide	No	No	Yes
NA	Proprietary epoxy resin	No	No	No
112945-52-5	Silica, amorphous treated	No	No	No
2426-08-6	Oxirane, (Butoxymethyl)-	No	No	No
9046-10-0	*Poly(oxy(methyl-1,2-ethanediyl)	No	No	No
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	No	No	No
1333-86-4	Carbon black	No	No	No

CAS # Hazardous Components (Chemical Name) Other US EPA or State Lists

1344-28-1	Aluminum oxide	TSCA: Yes - Inventory
NA	Proprietary epoxy resin	TSCA: Yes - Inventory
112945-52-5	Silica, amorphous treated	TSCA: Yes - Inventory
2426-08-6	Oxirane, (Butoxymethyl)-	TSCA: Yes - Inventory, 4 Test, 8A
9046-10-0	*Poly(oxy(methyl-1,2-ethanediyl)	TSCA: Yes - Inventory
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	TSCA: Yes - Inventory
1333-86-4	Carbon black	TSCA: Yes - Inventory

16. Other Information

Revision Date: 06/13/2017

Additional Information About This Product:

No data available.

Company Policy or

Disclaimer:

The information on this data sheet represents our current and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or the applicable technical bulletin, or which involves using the product in combination with any other product or any other process is the responsibility of the user.