

Page: 1 of 6

Revision: 06/13/2017 Supersedes Revision: 05/19/2016

Phone Number:

1. Product and Company Identification

Product Code: 3173 Product Name: 3173

Company Name: Appli-Tec, Inc

7 Industrial Way Unit 1 (603)685-0500

Salem, NH 03079

Web site address: www.appli-tec.com

Emergency Contact: Contact medical emergency services

Information: Call Chemtrec for Transport Info. (800)424-9300

Intended Use: Adhesive

2. Hazards Identification

Acute Toxicity: Oral, Category 4
Skin Corrosion/Irritation, Category 1A
Serious Eye Damage/Eye Irritation, Category 1

Skin Sensitization, Category 1





GHS Signal Word: Danger

GHS Hazard Phrases: H302 - Harmful if swallowed.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

GHS Precaution Phrases: P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P260 - Do not breathe vaports, mist, or spray.

P280 - Wear protective gloves/eye protection/face protection.

P272 - Contaminated work clothing should not be allowed out of the workplace.

GHS Response Phrases: P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all

contaminated clothing. Rinse skin with water/shower. P363 - Wash contaminated clothing before reuse.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing.

P310 - Immediately call a poison control center or doctor.

P333+313 - If skin irritation or rash occurs, seek medical advice/attention.

GHS Storage and Disposal P501 - Dispose of contents/container according to national and local regulations.

Phrases: P405 - Store locked up.

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.



Page: 2 of 6

Revision: 06/13/2017 Supersedes Revision: 05/19/2016

Potential Health Effects (Acute and Chronic):

Harmful if inhaled. Inhalation:

Skin Contact: Causes skin burns. May cause allergic skin reaction. Eye Contact: Causes eye burns. Causes serious eye damage.

Harmful if swallowed. Ingestion: **Additional Information** No data available.

3. Composition/Information on Ingredients

CAS#	Hazardous Components (Chemical Name)	Concentration
1344-28-1	Aluminum oxide	60.0 -80.0 %
25068-38-6	Bisphenol-a based epoxy resin	15.0 -30.0 %
9046-10-0	*Poly(oxy(methyl-1,2-ethanediyl)	1.0 -10.0 %
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	1.0 -5.0 %
2426-08-6	Oxirane, (Butoxymethyl)-	0.0 -1.0 %
1333-86-4	Carbon black	0.0 -1.0 %
65997-17-3	Fibrous glass	0.1 -1.0 %

Additional Information Exact percentages have been withheld as a trade secret.

4. First Aid Measures

Emergency and First Aid

Procedures:

In Case of Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get immediate medical attention.

Remove contaminated clothing. Wash skin with soap and water. Get medical In Case of Skin Contact:

attention. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes, occasionally In Case of Eye Contact:

lifting the upper and lower eyelids. Get medical aid immediately.

Do NOT induce vomiting. Never give anything by mouth to an unconscious In Case of Ingestion:

person. Get medical attention immediately.

5. Fire Fighting Measures

Flash Pt: > 93.00 C

Explosive Limits: LEL: No data. UEL: No data.

Autoignition Pt: No data.

Suitable Extinguishing

Use water spray, dry chemical, carbon dioxide, or appropriate foam.

Fire Fighting Instructions: As in any fire, wear a self-contained breathing apparatus in pressure-demand,

MSHA/NIOSH (approved or equivalent), and full protective gear.

Flammable Properties and No data available.

Hazards:

Media:

Hazardous Combustion

No data available.

Products:



Page: 3 of 6

Revision: 06/13/2017 Supersedes Revision: 05/19/2016

6. Accidental Release Measures

Material Is Released Or Spilled:

Steps To Be Taken In Case Ensure adequate ventilation. Isolate area and deny entry. Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Use proper personal protective equipment as indicated in Section 8. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

7. Handling and Storage

Precautions To Be Taken in Handling:

Use only with adequate ventilation. Avoid contact with eyes, skin, and clothing. Do not breathe dust, mist, or vapor. Wash thoroughly after handling.

Precautions To Be Taken

Store at <= -60deg.C.

in Storing:

8. Exposure	Contro	Is/Persona	I Protec	tion
-------------	--------	------------	----------	------

CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
1344-28-1	Aluminum oxide	PEL: 15 (dust); 5 (resp.) mg/m3	TLV: 10 mg/m3 (E)	No data.
25068-38-6	Bisphenol-a based epoxy resin	No data.	No data.	No data.
9046-10-0	*Poly(oxy(methyl-1,2-ethanediyl)	No data.	No data.	No data.
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamin e)	No data.	No data.	No data.
2426-08-6	Oxirane, (Butoxymethyl)-	PEL: 50 ppm	TLV: 3 ppm	No data.
1333-86-4	Carbon black	PEL: 3.5 mg/m3	TLV: 3 mg/m3 (IHL)	No data.
65997-17-3	Fibrous glass	No data.	TLV: 1 f/cc (fibers)	No data.

Respiratory Equipment

(Specify Type):

Use a NIOSH/MSHA or European Standard EN 149 approved respirator if

exposure limits are exceeded or if irritation or other symptoms are experienced.

Eye Protection: Safety glasses.

Protective Gloves: Wear appropriate protective gloves to prevent skin exposure. Other Protective Clothing: Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls

(Ventilation etc.):

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use process enclosure, local exhaust ventilation, or

other engineering controls to control airborne levels below recommended

exposure limits.

Work/Hygienic/Maintenanc Handle in accordance with good industrial hygiene and safety practice. Wash

e Practices:

hands before breaks and at the end of workday.

Page: 4 of 6

Revision: 06/13/2017 Supersedes Revision: 05/19/2016

9. Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: Appearance: Black. Paste.

Odor: amine-like.

Melting Point:No data.Boiling Point:No data.Flash Pt:> 93.00 CEvaporation Rate:No data.

Flammability (solid, gas): No data available.

Explosive Limits: LEL: No data. UEL: No data.

Vapor Pressure (vs. Air or No data.

mm Hg):

Vapor Density (vs. Air = 1): No data. Specific Gravity (Water = ~2.2

1):

Solubility in Water: No data.

Percent Volatile: No data.

Autoignition Pt: No data.

10. Stability and Reactivity

Stability: Unstable [X] Stable []

Conditions To Avoid - Product will cure at ambient temperatures. Keep in cold storage until ready to

Instability: use.

Incompatibility - Materials Strong oxidizing agents, Strong acids, Strong bases.

To Avoid:

Hazardous Decomposition Carbon oxides, Nitrogen oxides.

or Byproducts:

Possibility of Hazardous Will occur [] Will not occur [X]

Reactions:

Conditions To Avoid - No data available.

Hazardous Reactions:

11. Toxicological Information

Toxicological Information: No data available.

Irritation or Corrosion: Serious eye damage/irritation. Skin corrosion/irritation.

Sensitization: Skin sensitization.

12. Ecological Information

No data available.

13. Disposal Considerations

Waste Disposal Method: Observe all federal, state, and local environmental regulations.

14. Transport Information



Page: 5 of 6

Revision: 06/13/2017 Supersedes Revision: 05/19/2016

LAND TRANSPORT (US DOT):

DOT Proper Shipping Polyamines, liquid, corrosive, n.o.s. (Polyoxypropylenediamine,

Name: 3,3'-oxybis(ethyleneoxy)bis(propylamine))

DOT Hazard Class: 8 CORROSIVE

UN/NA Number: UN2735 Packing Group: II



MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Polyamines, liquid, corrosive, n.o.s. (Polyoxypropylenediamine,

3,3'-oxybis(ethyleneoxy)bis(propylamine))

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Polyamines, liquid, corrosive, n.o.s. (Polyoxypropylenediamine,

Name: 3,3'-oxybis(ethyleneoxy)bis(propylamine))

15. Regulatory Information

EPA SARA (Superfund	Amendments and Reauthorization Act of 1986) Lists
---------------------	---

CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
1344-28-1	Aluminum oxide	No	No	Yes
25068-38-6	Bisphenol-a based epoxy resin	No	No	No
9046-10-0	*Poly(oxy(methyl-1,2-ethanediyl)	No	No	No
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	No	No	No
2426-08-6	Oxirane, (Butoxymethyl)-	No	No	No
1333-86-4	Carbon black	No	No	No
65997-17-3	Fibrous glass	No	No	No

CAS # Hazardous Components (Chemical Name) Other US EPA or State Lists

1344-28-1	Aluminum oxide	TSCA: Yes - Inventory
25068-38-6	Bisphenol-a based epoxy resin	TSCA: Yes - Inventory
9046-10-0	*Poly(oxy(methyl-1,2-ethanediyl)	TSCA: Yes - Inventory
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	TSCA: Yes - Inventory
2426-08-6	Oxirane, (Butoxymethyl)-	TSCA: Yes - Inventory, 4

2426-08-6 Oxirane, (Butoxymethyl)- TSCA: Yes - Inventory, 4 Test, 8A 1333-86-4 Carbon black TSCA: Yes - Inventory

65997-17-3 Fibrous glass TSCA: Yes - Inventory

16. Other Information

Revision Date: 06/13/2017

Additional Information About This Product:

No data available.

Company Policy or

Disclaimer:

The information on this data sheet represents our current and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or the applicable technical bulletin, or which involves using the product in combination with any other product or any other process is the responsibility of the user.