

1. Product and Company Identification

Product Code: 3187A
Product Name: 3187A
Company Name: Appli-Tec, Inc
 7 Industrial Way Unit 1
 Salem, NH 03079
Phone Number: (603)685-0500

Web site address: www.appli-tec.com

Emergency Contact: Contact medical emergency services
Information: Call Chemtrec for Transport Info. (800)424-9300

Intended Use: Resin for two part adhesive

2. Hazards Identification

Flammable Liquids, Category 2
Skin Corrosion/Irritation, Category 2
Serious Eye Damage/Eye Irritation, Category 2
Skin Sensitization, Category 1
Germ Cell Mutagenicity, Category 1B
Carcinogenicity, Category 1B
Acute Toxicity: Oral, Category 4



GHS Signal Word: Danger

GHS Hazard Phrases: H225 - Highly flammable liquid and vapor.
 H302 - Harmful if swallowed.
 H315 - Causes skin irritation.
 H317 - May cause an allergic skin reaction.
 H319 - Causes serious eye irritation.
 H340 - May cause genetic defects .
 H350 - May cause cancer .

GHS Precaution Phrases: P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground/bond container and receiving equipment.
 P241 - Use explosion-proof electrical/ventilating/lighting/.../ equipment.
 P242 - Use only non-sparking tools.
 P243 - Take precautionary measures against static discharge.
 P261 - Avoid breathing vapors, mist, or spray.
 P264 - Wash skin thoroughly after handling.
 P270 - Do not eat, drink or smoke when using this product.
 P272 - Contaminated work clothing should not be allowed out of the workplace.
 P280 - Wear protective gloves/eye protection/face protection.

GHS Response Phrases: P301+312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
 P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
 P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+313 - IF exposed or concerned: Get medical attention/advice.
P330 - Rinse mouth.
P333+313 - If skin irritation or rash occurs, seek medical advice/attention.
P337+313 - If eye irritation persists, get medical advice/attention.
P362 - Take off contaminated clothing and wash before re-use.
P370+378 - In case of fire, use appropriate media to extinguish.

GHS Storage and Disposal Phrases:

P403+235 - Store in cool/well-ventilated place.
P405 - Store locked up.
P501 - Dispose of contents/container according to national and local regulations.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute and Chronic):

Inhalation: Harmful if inhaled.
Skin Contact: Causes skin irritation. May cause allergic skin reaction.
Eye Contact: Causes eye irritation.
Ingestion: Harmful if swallowed.
Additional Information No data available.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
25068-38-6	Bisphenol-a based epoxy resin	10.0 -20.0 %
79-20-9	Methyl acetate (Methyl ester of acetic acid; Abietic acid methyl ester)	10.0 -20.0 %
110-43-0	2-Heptanone	5.0 -10.0 %
123-86-4	Butyl acetate	1.0 -5.0 %
64742-95-6	SC-100 Solvent	0.0 -1.0 %
8052-41-3	Stoddard solvent	0.0 -1.0 %

Additional Information Exact percentages have been withheld as a trade secret.

4. First Aid Measures

Emergency and First Aid Procedures:

In Case of Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.
In Case of Skin Contact: Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash contaminated clothing before reuse.
In Case of Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention/advice.
In Case of Ingestion: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical advice/attention.
Note to Physician: Treat symptomatically and supportively.

5. Fire Fighting Measures

Flash Pt: < 0.00 C

Explosive Limits: LEL: No data. UEL: No data.

Autoignition Pt: No data.

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or appropriate foam.

Fire Fighting Instructions: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear.

Flammable Properties and Hazards: No data available.

Hazardous Combustion Products: No data available.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled: Ensure adequate ventilation. Isolate area and deny entry. Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Use proper personal protective equipment as indicated in Section 8. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

7. Handling and Storage

Precautions To Be Taken in Handling: Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Use spark-proof tools and explosion proof equipment. Use only with adequate ventilation. Keep away from heat, sparks and flame. Ground and bond containers when transferring material.

Precautions To Be Taken in Storing: Keep away from heat, sparks and flame. Store in a cool, dry, well-ventilated area away from incompatible substances.

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
25068-38-6	Bisphenol-a based epoxy resin	No data.	No data.	No data.
79-20-9	Methyl acetate (Methyl ester of acetic acid; Abietic acid methyl ester)	PEL: 200 ppm	TLV: 200 ppm STEL: 250 ppm	No data.
110-43-0	2-Heptanone	PEL: 100 ppm	TLV: 50 ppm	No data.
123-86-4	Butyl acetate	PEL: 150 ppm	TLV: 150 ppm STEL: 200 ppm	No data.
64742-95-6	SC-100 Solvent	No data.	No data.	No data.
8052-41-3	Stoddard solvent	PEL: 500 ppm	TLV: 100 ppm	No data.

Respiratory Equipment (Specify Type): Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Eye Protection: Safety glasses.

Protective Gloves: Wear appropriate protective gloves to prevent skin exposure.

Other Protective Clothing: Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation etc.): Use process enclosure, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Work/Hygienic/Maintenance Practices: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. Physical and Chemical Properties

Physical States:	[<input type="checkbox"/>] Gas [<input checked="" type="checkbox"/>] Liquid [<input type="checkbox"/>] Solid	
Appearance and Odor:	Appearance: Opaque. Liquid. Odor: solvent odor.	
Melting Point:	No data.	
Boiling Point:	No data.	
Flash Pt:	< 0.00 C	
Evaporation Rate:	No data.	
Flammability (solid, gas):	No data available.	
Explosive Limits:	LEL: No data.	UEL: No data.
Vapor Pressure (vs. Air or mm Hg):	No data.	
Vapor Density (vs. Air = 1):	No data.	
Specific Gravity (Water = 1):	~1.5	
Solubility in Water:	No data.	
Percent Volatile:	N.A.	
Autoignition Pt:	No data.	

10. Stability and Reactivity

Stability:	Unstable [<input type="checkbox"/>] Stable [<input checked="" type="checkbox"/>]	
Conditions To Avoid - Instability:	Heat, flames and sparks.	
Incompatibility - Materials To Avoid:	No data available.	
Hazardous Decomposition or Byproducts:	Carbon oxides.	
Possibility of Hazardous Reactions:	Will occur [<input type="checkbox"/>] Will not occur [<input checked="" type="checkbox"/>]	
Conditions To Avoid - Hazardous Reactions:	No data available.	

11. Toxicological Information

Toxicological Information: No data available.
Sensitization: Skin sensitization.

12. Ecological Information

No data available.

13. Disposal Considerations

Waste Disposal Method: Observe all federal, state, and local environmental regulations.
Waste Disposal Method: D001

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Paint.
DOT Hazard Class: 3 FLAMMABLE LIQUID
UN/NA Number: UN1263 **Packing Group:** II



MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Paint.

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Paint.

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
25068-38-6	Bisphenol-a based epoxy resin	No	No	No
79-20-9	Methyl acetate (Methyl ester of acetic acid; Abietic acid methyl ester)	No	No	No
110-43-0	2-Heptanone	No	No	No
123-86-4	Butyl acetate	No	Yes 5000 LB	No
64742-95-6	SC-100 Solvent	No	No	No
8052-41-3	Stoddard solvent	No	No	No

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
25068-38-6	Bisphenol-a based epoxy resin	TSCA: Yes - Inventory
79-20-9	Methyl acetate (Methyl ester of acetic acid; Abietic acid methyl ester)	TSCA: Yes - Inventory, 4 Test, 8A PAIR
110-43-0	2-Heptanone	TSCA: Yes - Inventory
123-86-4	Butyl acetate	TSCA: Yes - Inventory, 4 Test
64742-95-6	SC-100 Solvent	TSCA: Yes - Inventory
8052-41-3	Stoddard solvent	TSCA: Yes - Inventory

16. Other Information

Revision Date: 07/26/2016

Additional Information No data available.

About This Product:

Company Policy or

Disclaimer:

The information on this data sheet represents our current and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or the applicable technical bulletin, or which involves using the product in combination with any other product or any other process is the responsibility of the user.