

1. Product and Company Identification

Product Code: 3236
Product Name: 3236
Company Name: Appli-Tec, Inc
 7 Industrial Way Unit 1
 Salem, NH 03079
Phone Number: (603)685-0500

Web site address: www.appli-tec.com

Emergency Contact: Contact medical emergency services
Information: Call Chemtrec for Transport Info. (800)424-9300

Intended Use: Adhesive

2. Hazards Identification

Skin Corrosion/Irritation, Category 2
Serious Eye Damage/Eye Irritation, Category 1
Skin Sensitization, Category 1
Aquatic Toxicity (Chronic), Category 2



GHS Signal Word: Danger

GHS Hazard Phrases: H315 - Causes skin irritation.
 H317 - May cause an allergic skin reaction.
 H318 - Causes serious eye damage.
 H411 - Toxic to aquatic life with long lasting effects.

GHS Precaution Phrases: P261 - Avoid breathing vapors, mist, or spray.
 P264 - Wash hands thoroughly after handling.
 P272 - Contaminated work clothing should not be allowed out of the workplace.
 P273 - Avoid release to the environment.
 P280 - Wear protective gloves/eye protection/face protection.

GHS Response Phrases: P302+352 - IF ON SKIN: Wash with plenty of soap and water.
 P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 - Immediately call a POISON CENTER or doctor/physician.
 P333+313 - If skin irritation or rash occurs, seek medical advice/attention.
 P362 - Take off contaminated clothing and wash before re-use.
 P391 - Collect spillage.

GHS Storage and Disposal Phrases: P501 - Dispose of contents/container according to national and local regulations.

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute and Chronic):

Inhalation: Harmful if inhaled.

Skin Contact: Causes skin burns. May cause allergic skin reaction.

Eye Contact: Causes eye burns. Causes serious eye damage.

Ingestion: Harmful if swallowed.

Additional Information No data available.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
25068-38-6	Bisphenol-a based epoxy resin	5.0 -25.0 %
68154-62-1	Fatty acids, c18-unsaturated, dimers, polymers with oleic acid and triethylene tetramine	5.0 -20.0 %
9003-36-5	Phenol, polymer with (chloromethyl)oxirane and formaldehyde	5.0 -10.0 %
2425-79-8	1,4-Butanedioldiglycidyl ether	0.1 -5.0 %
7195-44-0	Bis(2,3-epoxypropyl) terephthalate	0.1 -5.0 %
10563-29-8	N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine	0.1 -5.0 %
111-40-0	Diethylenetriamine	0.1 -5.0 %
80-05-7	4,4'-Isopropylidenediphenol	0.1 -1.0 %
7237-83-4	Tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate	0.0 -1.0 %

Additional Information Exact percentages have been withheld as a trade secret.

4. First Aid Measures

Emergency and First Aid Procedures:

- In Case of Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.
- In Case of Skin Contact:** Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash contaminated clothing before reuse.
- In Case of Eye Contact:** Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention/advice.
- In Case of Ingestion:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical advice/attention.

5. Fire Fighting Measures

- Flash Pt:** > 100.00 C
- Explosive Limits:** LEL: No data. UEL: No data.
- Autoignition Pt:** No data.
- Suitable Extinguishing Media:** Use water spray, dry chemical, carbon dioxide, or appropriate foam.
- Fire Fighting Instructions:** As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear.
- Flammable Properties and Hazards:** No data available.
- Hazardous Combustion Products:** No data available.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled: Ensure adequate ventilation. Isolate area and deny entry. Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Use proper personal protective equipment as indicated in Section 8. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

7. Handling and Storage

Precautions To Be Taken in Handling: Avoid contact with eyes, skin, and clothing. Avoid ingestion and inhalation. Use only in a well ventilated area. Normal measures for preventive fire protection.

Precautions To Be Taken in Storing: Store at -40 deg.C.

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
25068-38-6	Bisphenol-a based epoxy resin	No data.	No data.	No data.
68154-62-1	Fatty acids, c18-unsaturated, dimers, polymers with oleic acid and triethylene tetramine	No data.	No data.	No data.
9003-36-5	Phenol, polymer with (chloromethyl)oxirane and formaldehyde	No data.	No data.	No data.
2425-79-8	1,4-Butanedioldiglycidyl ether	No data.	No data.	No data.
7195-44-0	Bis(2,3-epoxypropyl) terephthalate	No data.	No data.	No data.
10563-29-8	N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine	No data.	No data.	No data.
111-40-0	Diethylenetriamine	No data.	TLV: 1 ppm	No data.
80-05-7	4,4'-Isopropylidenediphenol	No data.	No data.	No data.
7237-83-4	Tris(oxiranylmethyl)benzene-1,2,4-tricarboxylate	No data.	No data.	No data.

Respiratory Equipment (Specify Type): Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Eye Protection: Safety glasses.

Protective Gloves: Wear appropriate protective gloves to prevent skin exposure.

Other Protective Clothing: Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation etc.): Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

9. Physical and Chemical Properties

Physical States:	[] Gas [X] Liquid [] Solid	
Appearance and Odor:	Appearance: Gray. Paste. Odor: amine-like.	
Melting Point:	No data.	
Boiling Point:	No data.	
Flash Pt:	> 100.00 C	
Evaporation Rate:	No data.	
Flammability (solid, gas):	No data available.	
Explosive Limits:	LEL: No data.	UEL: No data.
Vapor Pressure (vs. Air or mm Hg):	No data.	
Vapor Density (vs. Air = 1):	No data.	
Specific Gravity (Water = 1):	~1.7	
Solubility in Water:	No data.	
Percent Volatile:	No data.	
Autoignition Pt:	No data.	

10. Stability and Reactivity

Stability:	Unstable [X] Stable []
Conditions To Avoid - Instability:	Product will cure at ambient temperatures. Keep in cold storage until ready to use.
Incompatibility - Materials To Avoid:	Strong acids, Strong bases, Strong oxidizing agents.
Hazardous Decomposition or Byproducts:	Carbon oxides.
Possibility of Hazardous Reactions:	Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions:	No data available.

11. Toxicological Information

Toxicological Information:	No data available.
Irritation or Corrosion:	Serious eye damage/irritation. Skin corrosion/irritation.
Sensitization:	Skin sensitization.

12. Ecological Information

General Ecological Information:	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
--	---

13. Disposal Considerations

Waste Disposal Method: Observe all federal, state, and local environmental regulations.

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (Bisphenol A Epoxy Resin).
DOT Hazard Class: 9 CLASS 9
UN/NA Number: UN3082 **Packing Group:** III



LAND TRANSPORT (European ADR/RID):

ADR/RID Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (Bisphenol A Epoxy Resin).

MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (Bisphenol A Epoxy Resin).

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (Bisphenol A Epoxy Resin).

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
25068-38-6	Bisphenol-a based epoxy resin	No	No	No
68154-62-1	Fatty acids, c18-unsaturated, dimers, polymers with oleic acid and triethylene tetramine	No	No	No
9003-36-5	Phenol, polymer with (chloromethyl)oxirane and formaldehyde	No	No	No
2425-79-8	1,4-Butanedioldiglycidyl ether	No	No	No
7195-44-0	Bis(2,3-epoxypropyl) terephthalate	No	No	No
10563-29-8	N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine	No	No	No
111-40-0	Diethylenetriamine	No	No	No
80-05-7	4,4'-Isopropylidenediphenol	No	No	Yes
7237-83-4	Tris(oxiranymethyl) benzene-1,2,4-tricarboxylate	No	No	No

Other US EPA or State Lists

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
25068-38-6	Bisphenol-a based epoxy resin	TSCA: Yes - Inventory
68154-62-1	Fatty acids, c18-unsaturated, dimers, polymers with oleic acid and triethylene tetramine	TSCA: Yes - Inventory
9003-36-5	Phenol, polymer with (chloromethyl)oxirane and formaldehyde	TSCA: Yes - Inventory
2425-79-8	1,4-Butanedioldiglycidyl ether	TSCA: Yes - Inventory, 4 Test, 8A
7195-44-0	Bis(2,3-epoxypropyl) terephthalate	TSCA: No
10563-29-8	N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine	TSCA: Yes - Inventory

111-40-0	Diethylenetriamine	TSCA: Yes - Inventory
80-05-7	4,4'-Isopropylidenediphenol	TSCA: Yes - Inventory, 4 Test
7237-83-4	Tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate	TSCA: No

16. Other Information

Revision Date: 04/11/2016

Additional Information About This Product: No data available.

Company Policy or Disclaimer: The information on this data sheet represents our current and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or the applicable technical bulletin, or which involves using the product in combination with any other product or any other process is the responsibility of the user.