

Page: 1 of 5

Revision: 10/18/2017

1. Product and Company Identification

Product Code: 3282 Product Name: 3282

Company Name: Appli-Tec, Inc Phone Number: 7 Industrial Way Unit 1 (603)685-0500

Salem, NH 03079

Web site address: www.appli-tec.com

Emergency Contact: Contact medical emergency services

Information: Call Chemtrec for Transport Info. (800)424-9300

Intended Use: Adhesive

2. Hazards Identification

Skin Corrosion/Irritation, Category 1B Serious Eye Damage/Eye Irritation, Category 1 Skin Sensitization, Category 1





GHS Signal Word: Danger

GHS Hazard Phrases: H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

GHS Precaution Phrases: P260 - Do not breathe vapors, mist, or spray.

P264 - Wash hands thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves/eye protection/face protection.

GHS Response Phrases: P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all

contaminated clothing. Rinse skin with water/shower.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER or doctor/physician.

P333+313 - If skin irritation or rash occurs, seek medical advice/attention.

P363 - Wash contaminated clothing before reuse.

GHS Storage and Disposal P405 - Store locked up.

Phrases: P501 - Dispose of contents/container according to national and local regulations.

Emergency Overview:

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute and Chronic):

Inhalation: Harmful if inhaled.

Skin Contact: Causes skin burns. May cause allergic skin reaction. **Eye Contact:** Causes eye burns. Causes serious eye damage.

Ingestion:Harmful if swallowed.Additional InformationNo data available.

Licensed to Appli-Tec GHS format



Page: 2 of 5

Revision: 10/18/2017

3. Composition/Information on Ingredients

CAS#	Hazardous Components (Chemical Name)	Concentration
1344-28-1	Aluminum oxide	65.0 -75.0 %
25068-38-6	Bisphenol-a based epoxy resin	15.0 -30.0 %
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	1.0 -10.0 %
2426-08-6	Oxirane, (Butoxymethyl)-	0.0 -1.0 %
1333-86-4	Carbon black	0.0 -1.0 %

Additional Information Exact percentages have been withheld as a trade secret.

4. First Aid Measures

Emergency and First Aid

Procedures:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is In Case of Inhalation:

difficult, give oxygen. Get immediate medical attention.

Remove contaminated clothing. Wash skin with soap and water. Get medical In Case of Skin Contact:

attention. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes, occasionally In Case of Eye Contact:

lifting the upper and lower eyelids. Get medical attention/advice.

Do NOT induce vomiting. Never give anything by mouth to an unconscious In Case of Ingestion:

person. Get medical advice/attention.

5. Fire Fighting Measures

Flash Pt: > 93.00 C

LEL: No data. **Explosive Limits:** UEL: No data.

Autoignition Pt: No data.

Suitable Extinguishing

Media:

Use water spray, dry chemical, carbon dioxide, or appropriate foam.

Fire Fighting Instructions: As in any fire, wear a self-contained breathing apparatus in pressure-demand,

MSHA/NIOSH (approved or equivalent), and full protective gear.

Flammable Properties and No data available.

Hazards:

Hazardous Combustion

No data available.

Products:

6. Accidental Release Measures

Material Is Released Or

Spilled:

Steps To Be Taken In Case Ensure adequate ventilation. Isolate area and deny entry. Do not let product enter drains. Prevent further leakage or spillage if safe to do so. Use proper personal protective equipment as indicated in Section 8. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

7. Handling and Storage

Precautions To Be Taken

in Handling:

Avoid contact with eyes, skin, and clothing. Avoid ingestion and inhalation. Use

with adequate ventilation.

Precautions To Be Taken

in Storing:

Store at <= -40deg.C.

Licensed to Appli-Tec **GHS** format



Page: 3 of 5

Revision: 10/18/2017

8.	Exposure (Controls	s/Personal	Protection

CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
1344-28-1	Aluminum oxide	PEL: 15 (dust); 5 (resp.) mg/m3	TLV: 10 mg/m3 (E)	No data.
25068-38-6	Bisphenol-a based epoxy resin	No data.	No data.	No data.
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamin e)	No data.	No data.	No data.
2426-08-6	Oxirane, (Butoxymethyl)-	PEL: 50 ppm	TLV: 3 ppm	No data.
1333-86-4	Carbon black	PEL: 3.5 mg/m3	TLV: 3 mg/m3 (IHL)	No data.

Respiratory Equipment

Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

(Specify Type): **Eye Protection:**

Safety glasses.

Protective Gloves: Engineering Controls (Ventilation etc.):

Wear appropriate protective gloves to prevent skin exposure. Other Protective Clothing: Wear appropriate protective clothing to prevent skin exposure. Use adequate general or local exhaust ventilation to keep airborne

concentrations below the permissible exposure limits. Facilities storing or

utilizing this material should be equipped with an eyewash facility and a safety

shower.

Work/Hygienic/Maintenanc Handle in accordance with good industrial hygiene and safety practice. Wash

e Practices: thoroughly after handling.

9. Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid

Appearance: Black. Liquid. Appearance and Odor:

Odor: weak odor.

No data. **Melting Point: Boiling Point:** No data. Flash Pt: > 93.00 C No data. **Evaporation Rate:**

Flammability (solid, gas): No data available.

Explosive Limits: LEL: No data. UEL: No data.

Vapor Pressure (vs. Air or No data.

mm Hg):

Vapor Density (vs. Air = 1): No data. Specific Gravity (Water =

1):

Solubility in Water: No data. Percent Volatile: No data. **Autoignition Pt:** No data.

Licensed to Appli-Tec **GHS** format



Page: 4 of 5

Revision: 10/18/2017

10. Stability and Reactivity

Unstable [X] Stable [] Stability:

Product will cure at ambient temperatures. Keep in cold storage until ready to **Conditions To Avoid -**

Instability:

use.

Incompatibility - Materials Strong oxidizing agents, Strong reducing agents.

Hazardous Decomposition Carbon oxides, Nitrogen oxides.

or Byproducts:

Possibility of Hazardous Will occur [] Will not occur [X]

Reactions:

To Avoid:

Conditions To Avoid -No data available.

Hazardous Reactions:

11. Toxicological Information

Toxicological Information: No data available.

Serious eye damage/irritation. Skin corrosion/irritation. **Irritation or Corrosion:**

Sensitization: Skin sensitization.

12. Ecological Information

No data available.

13. Disposal Considerations

Observe all federal, state, and local environmental regulations. **Waste Disposal Method:**

14. Transport Information

CORROSIVE

LAND TRANSPORT (US DOT):

DOT Proper Shipping

Amines, liquid, corrosive, n.o.s. (Diethylene glycol di-(3-aminopropyl) ether)

Name:

DOT Hazard Class: 8

UN2735 UN/NA Number: Packing Group: Ш



MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Amines, liquid, corrosive, n.o.s. (Diethylene glycol di-(3-aminopropyl) ether)

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Amines, liquid, corrosive, n.o.s. (Diethylene glycol di-(3-aminopropyl) ether)

Name:

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
1344-28-1	Aluminum oxide	No	No	Yes
25068-38-6	Bisphenol-a based epoxy resin	No	No	No
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	No	No	No
2426-08-6	Oxirane, (Butoxymethyl)-	No	No	No
1333-86-4	Carbon black	No	No	No

Licensed to Appli-Tec **GHS** format



Page: 5 of 5

Revision: 10/18/2017

CAS # Hazardous Components (Chemical Name)	Other US EPA or State Lists
--	-----------------------------

1344-28-1Aluminum oxideTSCA: Inventory25068-38-6Bisphenol-a based epoxy resinTSCA: Inventory4246-51-93,3'-Oxybis(ethyleneoxy)bis(propylamine)TSCA: Inventory

2426-08-6 Oxirane, (Butoxymethyl)- TSCA: Inventory, 4 Test, 8A

1333-86-4 Carbon black TSCA: Inventory

16. Other Information

Revision Date: 10/18/2017

Additional Information About This Product:

No data available.

Company Policy or Disclaimer:

The information on this data sheet represents our current and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or the applicable technical bulletin, or which involves using the product in combination with any other product or any other process is the responsibility of the user.

Licensed to Appli-Tec GHS format