

Page: 1 of 6

Revision: 08/12/2015

1. Product and Company Identification

Product Code: 5105A Product Name: 5105A

Company Name: Appli-Tec, Inc Phone Number: 7 Industrial Way Unit 1 (603)685-0500

Salem, NH 03079

Web site address: www.appli-tec.com

Emergency Contact: Contact medical emergency services

Information: Call Chemtrec for Transport Info. (800)424-9300

Intended Use: Resin for two part adhesive

2. Hazards Identification

Skin Corrosion/Irritation, Category 2

Serious Eye Damage/Eye Irritation, Category 2A

Skin Sensitization, Category 1

Specific Target Organ Toxicity (single exposure), Category 3
Specific Target Organ Toxicity (repeated exposure), Category 2





GHS Signal Word: Warning

GHS Hazard Phrases: H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H335 - May cause respiratory irritation.

H373 - May cause damage to through prolonged or repeated exposure.

GHS Precaution Phrases: P260 - Do not breathe vapors, mist, or spray.

P264 - Wash hands thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves/eye protection/face protection.

GHS Response Phrases: P302+352 - IF ON SKIN: Wash with plenty of soap and water.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTER or doctor/physician if you feel unwell. P333+313 - If skin irritation or rash occurs, seek medical advice/attention.

P337+313 - If eye irritation persists, get medical advice/attention. P362 - Take off contaminated clothing and wash before re-use.

GHS Storage and Disposal P403+233 - Store container tightly closed in well-ventilated place.

Phrases: P405 - Store locked up.

P501 - Dispose of contents/container according to national and local regulations.

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.



Page: 2 of 6

Revision: 08/12/2015

Potential Health Effects (Acute and Chronic):

Harmful if inhaled. Inhalation:

Skin Contact: Causes skin irritation. May cause allergic skin reaction.

Eye Contact: Causes eye irritation. Harmful if swallowed. Ingestion: **Additional Information** No data available.

3. Composition/Information on Ingredients

CAS#	Hazardous Components (Chemical Name)	Concentration
25068-38-6	Bisphenol-a based epoxy resin	80.0 -90.0 %
14228-73-0	Oxirane, 2,2'-[1,4-Cyclohexanediylbis(methyleneoxymethylene)	5.0 -10.0 %
NA	Proprietary epoxy resin	1.0 -5.0 %
64742-95-6	SC-100 Solvent	1.0 -5.0 %
1333-86-4	Carbon black	0.1 -1.0 %
67762-90-7	Siloxanes and silicones, di-me, reaction products	0.1 -1.0 %

Additional Information Exact percentages have been withheld as a trade secret.

4. First Aid Measures

Emergency and First Aid

with silica

Procedures:

In Case of Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get immediate medical attention.

Remove contaminated clothing. Wash skin with soap and water. Get medical In Case of Skin Contact:

attention. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes, occasionally In Case of Eye Contact:

lifting the upper and lower eyelids. Get medical attention/advice.

Do NOT induce vomiting. Never give anything by mouth to an unconscious In Case of Ingestion:

person. Get medical advice/attention.

5. Fire Fighting Measures

Flash Pt: > 93.00 C

Explosive Limits: LEL: No data. UEL: No data.

No data. **Autoignition Pt:**

Suitable Extinguishing

Use water spray, dry chemical, carbon dioxide, or appropriate foam. Media:

Fire Fighting Instructions: As in any fire, wear a self-contained breathing apparatus in pressure-demand,

MSHA/NIOSH (approved or equivalent), and full protective gear.

Flammable Properties and No data available.

Hazards:

Hazardous Combustion

No data available.

Products:

Page: 3 of 6

Revision: 08/12/2015

6. Accidental Release Measures

Material Is Released Or Spilled:

Steps To Be Taken In Case Ensure adequate ventilation. Isolate area and deny entry. Do not let product enter drains. Prevent further leakage or spillage if safe to do so. Use proper personal protective equipment as indicated in Section 8. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

7. Handling and Storage

Precautions To Be Taken

in Handling:

Avoid contact with eyes, skin, and clothing. Avoid ingestion and inhalation. Use

only with adequate ventilation.

Precautions To Be Taken

Store in a cool, dry, well-ventilated area away from incompatible substances.

in Storing:

8. Exposure Controls/Personal Protection

CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
25068-38-6	Bisphenol-a based epoxy resin	No data.	No data.	No data.
14228-73-0	Oxirane, 2,2'-[1,4-Cyclohexanediylbis(methylene oxymethylene)	No data.	No data.	No data.
NA	Proprietary epoxy resin	No data.	No data.	No data.
64742-95-6	SC-100 Solvent	No data.	No data.	No data.
1333-86-4	Carbon black	PEL: 3.5 mg/m3	TLV: 3 mg/m3 (IHL)	No data.
67762-90-7	Siloxanes and silicones, di-me, reaction products with silica	No data.	No data.	No data.

Respiratory Equipment

(Specify Type):

Use a NIOSH/MSHA or European Standard EN 149 approved respirator if

exposure limits are exceeded or if irritation or other symptoms are experienced.

Safety glasses. **Eye Protection:**

Wear appropriate protective gloves to prevent skin exposure. **Protective Gloves:** Other Protective Clothing: Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation etc.):

Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits. Facilities storing or

utilizing this material should be equipped with an eyewash facility and a safety

shower.

9. Physical and Chemical Properties

[X] Liquid [] Solid **Physical States:** [] Gas

Appearance: Black, Liquid. Appearance and Odor:

Odor: weak odor.

Melting Point: No data. **Boiling Point:** No data. Flash Pt: > 93.00 C **Evaporation Rate:** No data.

Flammability (solid, gas): No data available.

LEL: No data. UEL: No data. **Explosive Limits:**

Vapor Pressure (vs. Air or No data.

mm Hg):

Vapor Density (vs. Air = 1): No data.





Revision: 08/12/2015

Specific Gravity (Water = No data.

1):

Solubility in Water: No data.

Percent Volatile: No data.

Autoignition Pt: No data.

10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Conditions To Avoid - No data available.

Instability:

Incompatibility - Materials Strong oxidizing agents, Strong reducing agents.

To Avoid:

Hazardous Decomposition Carbon oxides, Nitrogen oxides.

or Byproducts:

Possibility of Hazardous Will occur [] Will not occur [X]

Reactions:

Conditions To Avoid - No data available.

Hazardous Reactions:

11. Toxicological Information

Toxicological Information: No data available. **Sensitization:** Skin sensitization.

12. Ecological Information

No data available.

13. Disposal Considerations

Waste Disposal Method: Observe all federal, state, and local environmental regulations.

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Not Regulated.

Name:

DOT Hazard Class: UN/NA Number:

MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Not Regulated.

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Not Regulated.

Name:

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
25068-38-6	Bisphenol-a based epoxy resin	No	No	No
14228-73-0	Oxirane,	No	No	No

2,2'-[1,4-Cyclohexanediylbis(methyleneoxymethyl

ene)

NA Proprietary epoxy resin No No No No 64742-95-6 SC-100 Solvent No No No



Page: 5 of 6

Revision: 08/12/2015

with silica

CAS # Hazardous Components (Chemical Name) Other US EPA or State Lists

25068-38-6 Bisphenol-a based epoxy resin TSCA: Yes - Inventory

14228-73-0 Oxirane, TSCA: Yes - Inventory, 4 Test, 8A

2,2'-[1,4-Cyclohexanediylbis(methyleneoxymethyl

ene)

NA Proprietary epoxy resin TSCA: Yes - Inventory 64742-95-6 SC-100 Solvent TSCA: Yes - Inventory 1333-86-4 Carbon black TSCA: Yes - Inventory

67762-90-7 Siloxanes and silicones, di-me, reaction products TSCA: Yes - Inventory, 8A, 8A PAIR

with silica

16. Other Information

Revision Date: 08/12/2015

Additional Information About This Product:

No data available.

Company Policy or Disclaimer:

The information on this data sheet represents our current and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or the applicable technical bulletin, or which involves using the product in combination with any other product or any other process is the responsibility of the user.