

Page: 1 of 6

Revision: 01/31/2023

1. Product and Company Identification

Product Code: 3428 Product Name: 3428

Company Name: Appli-Tec, Inc Phone Number: 7 Industrial Way Unit 1 (603)685-0500

Salem, NH 03079

Web site address: www.appli-tec.com

Emergency Contact: Contact medical emergency services

Information: Call Chemtrec for Transport Info. (800)424-9300

Intended Use: Adhesive

2. Hazards Identification

Skin Corrosion/Irritation, Category 1B Serious Eye Damage/Eye Irritation, Category 1 Skin Sensitization, Category 1 Aquatic Toxicity (Chronic), Category 2







GHS Signal Word: Danger

GHS Hazard Phrases: H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H411 - Toxic to aquatic life with long lasting effects.

GHS Precautionary P261 - Avoid breathing vapors,mist or spray. **Phrases:** P264 - Wash hands thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/eye protection/face protection.

GHS Response Phrases: P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all

contaminated clothing. Rinse skin with water/shower.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER or doctor/physician.

P333+313 - If skin irritation or rash occurs, seek medical advice/attention.

P363 - Wash contaminated clothing before reuse.

P391 - Collect spillage.

GHS Storage and Disposal P405 - Store locked up. P501 - Dispose of contents/container according to

Phrases: national and local regulations.

Emergency Overview:

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

Licensed to Appli-Tec GHS format



Page: 2 of 6

Revision: 01/31/2023

Inhalation: May cause respiratory irritation.

Skin Contact: Causes skin irritation. May cause allergic skin reaction.

Eye Contact:Causes eye irritation.Ingestion:Harmful if swallowed.Additional InformationNo data available.

3. Composition/Information on Ingredients

CAS#	Hazardous Components (Chemical Name)	Concentration
25068-38-6	Bisphenol-a based epoxy resin	45.0 -65.0 %
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	15.0 -20.0 %
26142-30-3	Epichlorohydrin-polyglycol reaction product	3.5 -8.0 %
3101-60-8	Oxirane, [[4-(1,1-Dimethylethyl)phenoxy]methyl]-	0.1 -5.0 %
1760-24-3	Aminoethyl aminopropyl trimethoxysilane	0.1 -2.0 %

Additional Information Exact percentages have been withheld as a trade secret.

4. First Aid Measures

Emergency and First Aid

Procedures:

In Case of Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get immediate medical attention.

In Case of Skin Contact: Remove contaminated clothing. Wash skin with soap and water. Get medical

attention. Wash contaminated clothing before reuse.

In Case of Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally

lifting the upper and lower eyelids. Get medical attention/advice.

In Case of Ingestion: Do NOT induce vomiting. Never give anything by mouth to an unconscious

person. Get medical advice/attention.

Note to Physician: Treat symptomatically and supportively.

5. Fire Fighting Measures

Flash Pt: > 93.00 C

Explosive Limits: LEL: No data. UEL: No data.

Autoignition Pt: No data.

Suitable Extinguishing Use water spray, dry chemical, carbon dioxide, or appropriate foam.

Media:

Fire Fighting Instructions: As in any fire, wear a self-contained breathing apparatus in pressure-demand,

MSHA/NIOSH (approved or equivalent), and full protective gear.

Flammable Properties and No data available.

Hazards:

Hazardous Combustion No data available.

Products:

Licensed to Appli-Tec GHS format



Page: 3 of 6

Revision: 01/31/2023

6. Accidental Release Measures

Material Is Released Or Spilled:

Steps To Be Taken In Case Ensure adequate ventilation. Isolate area and deny entry. Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Use proper personal protective equipment as indicated in Section 8. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

7. Handling and Storage

Precautions To Be Taken

in Handling:

Avoid contact with skin and eyes. Use with adequate ventilation. Avoid ingestion

and inhalation.

Precautions To Be Taken Store at <= -40deg.C.

in Storing:

	8. Exposure Co	ontrols/Personal Protection		
CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
25068-38-6	Bisphenol-a based epoxy resin	No data.	No data.	No data.
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamin e)	No data.	No data.	No data.
26142-30-3	Epichlorohydrin-polyglycol reaction product	No data.	No data.	No data.
3101-60-8	Oxirane, [[4-(1,1-Dimethylethyl)phenoxy]methyl]-	No data.	No data.	No data.
1760-24-3	Aminoethyl aminopropyl trimethoxysilane	No data.	No data.	No data.

Respiratory Equipment

(Specify Type): **Eye Protection:**

Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Safety glasses.

Wear appropriate protective gloves to prevent skin exposure. **Protective Gloves:** Other Protective Clothing: Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation etc.):

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use process enclosure, local exhaust ventilation, or

other engineering controls to control airborne levels below recommended

exposure limits.

Work/Hygienic/Maintenanc Handle in accordance with good industrial hygiene and safety practice. Wash

e Practices: thoroughly after handling.

9. Physical and Chemical Properties

[X] Liquid [] Solid **Physical States:** [] Gas

Appearance and Odor: Appearance: Pink, Paste.

Odor: Ammoniacal odor.

No data. pH: **Melting Point:** No data. **Boiling Point:** No data. > 93.00 C Flash Pt: No data. **Evaporation Rate:**

Flammability (solid,

gas):

No data available.

LEL: No data. UEL: No data. **Explosive Limits:**

No data. Vapor Pressure (vs. Air



Page: 4 of 6

Revision: 01/31/2023

or mm Hg):

Vapor Density (vs. Air = No data.

1):

Specific Gravity (Water = ~1.105

1):

No data. Solubility in Water: **Saturated Vapor** No data.

Concentration:

Octanol/Water Partition

No data.

Coefficient:

Autoignition Pt: No data. **Decomposition** No data.

Temperature:

Viscosity: No data.

Information with regard to primary physical hazard:

10. Stability and Reactivity

Stability: Unstable [X] Stable []

Conditions To Avoid -Product will cure at ambient temperatures. Keep in cold storage until ready to

Instability: use.

Incompatibility - Materials Strong oxidizing agents, acids, bases. To Avoid:

Hazardous Decomposition Carbon oxides, Nitrogen oxides, Undetermined organics.

or Byproducts:

Possibility of Hazardous Will not occur [X] Will occur []

Reactions:

Conditions To Avoid -No data available.

Hazardous Reactions:

11. Toxicological Information

Toxicological Information: No data available. Sensitization: Skin sensitization.

12. Ecological Information

No data available.

13. Disposal Considerations

Waste Disposal Method: Observe all federal, state, and local environmental regulations.

14. Transport Information

Licensed to Appli-Tec **GHS** format



Page: 5 of 6

Revision: 01/31/2023

LAND TRANSPORT (US DOT):

DOT Proper Shipping AMINES, LIQUID, CORROSIVE, N.O.S. Polyglycol diamine, Bisp[henol-A

Name: Epichlorhydri)

CORROSIVE DOT Hazard Class: 8

UN/NA Number: UN2735 Ш **Packing Group:**



MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (Polyglycol diamine, Bisphenol-A

Epichlorhydrin resin)

UN Number: UN2735 Ш **Packing Group:**

Hazard Class: 8 - CORROSIVE

IMDG MFAG Number:

Marine Pollutant: Yes

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (Polyglycol diamine, Bisphenol-A

Epichlorhydrin resin)

UN Number: UN2735 **Packing Group:** Ш

Hazard Class: 8 - CORROSIVE

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists Hamandaya Cammananta (Chamiaal Nama)

CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
25068-38-6	Bisphenol-a based epoxy resin	No	No	No
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	No	No	No
26142-30-3	Epichlorohydrin-polyglycol reaction product	No	No	No
3101-60-8	Oxirane, [[4-(1,1-Dimethylethyl)phenoxy]methyl]-	No	No	No
1760-24-3	Aminoethyl aminopropyl trimethoxysilane	No	No	No
CAS#	Hazardous Components (Chemical Name)	Other US EPA or	State Lists	
CAS# 25068-38-6	Hazardous Components (Chemical Name) Bisphenol-a based epoxy resin	Other US EPA or TSCA: Inventory	State Lists	
			State Lists	
25068-38-6	Bisphenol-a based epoxy resin	TSCA: Inventory	State Lists	
25068-38-6 4246-51-9	Bisphenol-a based epoxy resin 3,3'-Oxybis(ethyleneoxy)bis(propylamine)	TSCA: Inventory TSCA: Inventory		

Licensed to Appli-Tec **GHS** format



Page: 6 of 6

Revision: 01/31/2023

16. Other Information

Revision Date: 01/31/2023

Additional Information About This Product:

No data available.

Company Policy or Disclaimer:

The information on this data sheet represents our current and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or the applicable technical bulletin, or which involves using the product in combination with any other product or any other process is the responsibility of the user.

Licensed to Appli-Tec GHS format