

Page: 1 of 6

Revision: 04/28/2023

1. Product and Company Identification

Product Code: 5337A Product Name: 5337A

Company Name: Appli-Tec, Inc Phone Number: 7 Industrial Way Unit 1 (603)685-0500

Salem, NH 03079

Web site address: www.appli-tec.com

Emergency Contact: Contact medical emergency services

Information: Call Chemtrec for Transport Info. (800)424-9300

Intended Use: Resin for two part adhesive

2. Hazards Identification

Skin Corrosion/Irritation, Category 2

Serious Eye Damage/Eye Irritation, Category 2

Skin Sensitization, Category 1

Specific Target Organ Toxicity (single exposure), Category 3



GHS Signal Word: Warning

GHS Hazard Phrases: H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.

H335 - May cause respiratory irritation.

GHS Precautionary P261 - Avoid breathing vapors, mist or spray. **Phrases:** P264 - Wash hands thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves/eye protection/face protection.

GHS Response Phrases: P302+352 - IF ON SKIN: Wash with plenty of soap and water.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTER or doctor/physician if you feel unwell. P333+313 - If skin irritation or rash occurs, seek medical advice/attention.

P337+313 - If eye irritation persists, get medical advice/attention. P362 - Take off contaminated clothing and wash before re-use.

GHS Storage and Disposal P405 - Store locked up.

Phrases: P501 - Dispose of contents/container according to national and local regulations.

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.



Page: 2 of 6

Revision: 04/28/2023

Inhalation: Harmful if inhaled.

Skin Contact: Causes skin irritation. May cause allergic skin reaction.

Eye Contact:Causes eye irritation.Ingestion:Harmful if swallowed.Additional InformationNo data available.

3. Composition/Information on Ingredients

CAS#	Hazardous Components (Chemical Name)	Concentration
1344-28-1	Aluminum oxide	70.0 -90.0 %
25068-38-6	Bisphenol-a based epoxy resin	10.0 -20.0 %
67762-90-7	Siloxanes and silicones, di-me, reaction products with silica	0.1 -2.0 %
112-55-0	Dodecyl mercaptan (n-)	0.1 -1.0 %
1333-86-4	Carbon black	0.1 -1.0 %
78-83-1	Isobutyl alcohol	0.1 -1.0 %
107-98-2	2-Propanol, 1-Methoxy-	0.1 -1.0 %

Additional Information Exact percentages have been withheld as a trade secret.

4. First Aid Measures

Emergency and First Aid

Procedures:

In Case of Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get immediate medical attention.

In Case of Skin Contact: Remove contaminated clothing. Wash skin with soap and water. Get medical

attention. Wash contaminated clothing before reuse.

In Case of Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally

lifting the upper and lower eyelids. Get medical attention/advice.

In Case of Ingestion: Do NOT induce vomiting. Never give anything by mouth to an unconscious

person. Get medical aid immediately.

Note to Physician: Treat symptomatically and supportively.

5. Fire Fighting Measures

Flash Pt: > 93.00 C

Explosive Limits: LEL: No data. UEL: No data.

Autoignition Pt: No data.

Suitable Extinguishing

Media:

Use water spray, dry chemical, carbon dioxide, or appropriate foam.

Fire Fighting Instructions: As in any fire, wear a self-contained breathing apparatus in pressure-demand,

MSHA/NIOSH (approved or equivalent), and full protective gear.

Flammable Properties and No data available.

Hazards:

Hazardous Combustion No data available.

Products:



Page: 3 of 6

Revision: 04/28/2023

6. Accidental Release Measures

Material Is Released Or Spilled:

Steps To Be Taken In Case Ensure adequate ventilation. Isolate area and deny entry. Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Use proper personal protective equipment as indicated in Section 8. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

7. Handling and Storage

Precautions To Be Taken

in Handling:

Avoid contact with skin and eyes. Use only in a well-ventilated area. Avoid ingestion and inhalation. Normal measures for preventive fire protection.

Precautions To Be Taken

Store in a cool, dry, well-ventilated area away from incompatible substances.

in Storing:

8. Exposure Controls/Personal Protection							
CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits			
1344-28-1	Aluminum oxide	PEL: 15 (dust); 5 (resp.) mg/m3	TLV: 10 mg/m3 (E)	No data.			
25068-38-6	Bisphenol-a based epoxy resin	No data.	No data.	No data.			
67762-90-7	Siloxanes and silicones, di-me, reaction products with silica	No data.	No data.	No data.			
112-55-0	Dodecyl mercaptan (n-)	No data.	No data.	No data.			
1333-86-4	Carbon black	PEL: 3.5 mg/m3	TLV: 3 mg/m3 (IHL)	No data.			
78-83-1	Isobutyl alcohol	PEL: 100 ppm	TLV: 50 ppm	No data.			
107-98-2	2-Propanol, 1-Methoxy-	No data.	TLV: 100 ppm STEL: 150 ppm	No data.			

Respiratory Equipment

(Specify Type):

Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Safety glasses. **Eye Protection:**

Protective Gloves: Wear appropriate protective gloves to prevent skin exposure. Other Protective Clothing: Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation etc.):

Facilities storing or utilizing this material should be equipped with an evewash

facility and a safety shower.

Use process enclosure, local exhaust ventilation, or other engineering controls

to control airborne levels below recommended exposure limits.

Work/Hygienic/Maintenanc Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling.

e Practices:

9. Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid

Appearance: Black. Paste. Appearance and Odor:

Odor: weak odor.

No data. pH: **Melting Point:** No data. **Boiling Point:** No data. Flash Pt: > 93.00 C No data. **Evaporation Rate:**

Flammability (solid,

gas):

No data available.

UEL: No data. LEL: No data. **Explosive Limits:**

GHS format Licensed to Appli-Tec



Page: 4 of 6

Revision: 04/28/2023

Vapor Pressure (vs. Air

or mm Hg):

No data.

or min rig).

Vapor Density (vs. Air = No data.

1):

Specific Gravity (Water = ~2.38

1):

Solubility in Water: No data.

Saturated Vapor No data.

Concentration:

Octanol/Water Partition

No data.

Coefficient:

Autoignition Pt: No data.

Decomposition No data.

Temperature:

Viscosity: No data.

Information with regard to primary physical

hazard:

10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Conditions To Avoid -

Incompatible materials, Excess heat.

Instability:

Incompatibility - Materials Strong oxidizing agents, Strong acids, Strong bases.

To Avoid:

Hazardous Decomposition Carbon oxides.

or Byproducts:

Possibility of Hazardous Will occur [] Will not occur [X]

Reactions:

Conditions To Avoid - No data available.

Hazardous Reactions:



Page: 5 of 6

Revision: 04/28/2023

11. Toxicological Information

Toxicological Information: No data available.

Irritation or Corrosion: Skin and eye irritant.

Sensitization: Skin sensitization.

12. Ecological Information

General Ecological Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

Information: environment.

13. Disposal Considerations

Waste Disposal Method: Observe all federal, state, and local environmental regulations.

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping

Not Regulated.

Name:

DOT Hazard Class: UN/NA Number:



MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Environmentally Hazardous Substance, Liquid, n.o.s. (Liquid epoxy resin)

UN Number: UN3082 Packing Group: III

Hazard Class: 9 - CLASS 9

IMDG MFAG Number:

Marine Pollutant: Yes

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Environmentally Hazardous Substance, Liquid, n.o.s. (Liquid epoxy resin)

UN Number: UN3082 Packing Group: III

Hazard Class: 9 - CLASS 9

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
1344-28-1	Aluminum oxide	No	No	Yes
25068-38-6	Bisphenol-a based epoxy resin	No	No	No
67762-90-7	Siloxanes and silicones, di-me, reaction products with silica	No	No	No
112-55-0	Dodecyl mercaptan (n-)	No	No	No
1333-86-4	Carbon black	No	No	No
78-83-1	Isobutyl alcohol	No	Yes NA	No
107-98-2	2-Propanol, 1-Methoxy-	No	No	No

California Proposition 65



This product can expose you to chemicals including Carbon black and Ethylbenzene, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.



Page: 6 of 6

Revision: 04/28/2023

CAS#	Hazardous Components (Chemical Name)	Other US EPA or State Lists
1344-28-1	Aluminum oxide	TSCA: Inventory
25068-38-6	Bisphenol-a based epoxy resin	TSCA: Inventory
67762-90-7	Siloxanes and silicones, di-me, reaction products with silica	TSCA: Inventory, 8A, 8A PAIR
112-55-0	Dodecyl mercaptan (n-)	TSCA: Inventory
1333-86-4	Carbon black	TSCA: Inventory
		CA PROP.65: Yes: Canc.
78-83-1	Isobutyl alcohol	TSCA: Inventory
107-98-2	2-Propanol, 1-Methoxy-	TSCA: Inventory

16. Other Information

Revision Date: 04/28/2023

Additional Information About This Product:

No data available.

Company Policy or Disclaimer:

The information on this data sheet represents our current and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or the applicable technical bulletin, or which involves using the product in combination with any other product or any other process is the responsibility of the user.