

1. Product and Company Identification

Product Code: 3476
Product Name: 3476
Company Name: Appli-Tec, Inc
 7 Industrial Way Unit 1
 Salem, NH 03079
Phone Number: (603)685-0500
Web site address: www.appli-tec.com
Emergency Contact: Contact medical emergency services
Information: Call Chemtrec for Transport Info. (800)424-9300
Intended Use: Adhesive

2. Hazards Identification

Skin Corrosion/Irritation, Category 2
Serious Eye Damage/Eye Irritation, Category 1
Skin Sensitization, Category 1



GHS Signal Word: **Danger**

GHS Hazard Phrases: H315 - Causes skin irritation.
 H317 - May cause an allergic skin reaction.
 H318 - Causes serious eye damage.

GHS Precautionary Phrases: P261 - Avoid breathing vapors, mist or spray.
 P264 - Wash hands thoroughly after handling.
 P272 - Contaminated work clothing should not be allowed out of the workplace.
 P280 - Wear protective gloves/eye protection/face protection.

GHS Response Phrases: P302+352 - IF ON SKIN: Wash with plenty of soap and water.
 P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 - Immediately call a POISON CENTER or doctor/physician.
 P333+313 - If skin irritation or rash occurs, seek medical advice/attention.
 P362 - Take off contaminated clothing and wash before re-use.

GHS Storage and Disposal Phrases: P501 - Dispose of contents/container according to national and local regulations.

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

Inhalation: Harmful if inhaled.

Skin Contact: Causes skin burns. May cause allergic skin reaction.

Eye Contact: Causes eye burns. Causes serious eye damage.

Ingestion: Harmful if swallowed.

Additional Information No data available.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
7429-90-5	Aluminum	25.0 -35.0 %
28768-32-3	4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline]	25.0 -35.0 %
25068-38-6	Bisphenol-a based epoxy resin	15.0 -30.0 %
112-57-2	Tetraethylenepentamine	5.0 -10.0 %
7209-38-3	1,4-Bis(3-aminopropyl)piperazine	2.0 -10.0 %
NA	Modified Epoxy Resin	2.0 -10.0 %
112945-52-5	Silica, amorphous treated	0.1 -3.0 %
4067-16-7	3,6,9,12-Tetraazatetradecamethylenediamine	0.1 -3.0 %
65997-17-3	Fibrous glass	0.1 -1.0 %
112-24-3	1,2-Ethanediamine, N,N'-Bis(2-aminoethyl)-	0.1 -1.0 %
1333-86-4	Carbon black	0.1 -0.5 %

Additional Information Exact percentages have been withheld as a trade secret.

4. First Aid Measures

Emergency and First Aid Procedures:

- In Case of Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.
- In Case of Skin Contact:** Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash contaminated clothing before reuse.
- In Case of Eye Contact:** Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention/advice.
- In Case of Ingestion:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical advice/attention.
- Note to Physician:** Treat symptomatically and supportively.

5. Fire Fighting Measures

- Flash Pt:** > 93.00 C
- Explosive Limits:** LEL: No data. UEL: No data.
- Autoignition Pt:** No data.
- Suitable Extinguishing Media:** Use water spray, dry chemical, carbon dioxide, or appropriate foam.
- Fire Fighting Instructions:** As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear.
- Flammable Properties and Hazards:** No data available.
- Hazardous Combustion Products:** No data available.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled: Ensure adequate ventilation. Isolate area and deny entry. Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Use proper personal protective equipment as indicated in Section 8. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

7. Handling and Storage

Precautions To Be Taken in Handling: Wash thoroughly after handling. Avoid contact with eyes, skin, and clothing. Avoid ingestion and inhalation. Use with adequate ventilation. Normal measures for preventive fire protection.

Precautions To Be Taken in Storing: Store at <= -40deg.C.

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
7429-90-5	Aluminum	PEL: 15 (dust); 5 (resp.) mg/m3	TLV: 1 mg/m3 (resp.)	No data.
28768-32-3	4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline]	No data.	No data.	No data.
25068-38-6	Bisphenol-a based epoxy resin	No data.	No data.	No data.
112-57-2	Tetraethylenepentamine	No data.	No data.	No data.
7209-38-3	1,4-Bis(3-aminopropyl)piperazine	No data.	No data.	No data.
NA	Modified Epoxy Resin	No data.	No data.	No data.
112945-52-5	Silica, amorphous treated	No data.	No data.	No data.
4067-16-7	3,6,9,12-Tetraazatetradecamethylenediamine	No data.	No data.	No data.
65997-17-3	Fibrous glass	No data.	TLV: 1 f/cc (fibers)	No data.
112-24-3	1,2-Ethanediamine, N,N'-Bis(2-aminoethyl)-	No data.	No data.	No data.
1333-86-4	Carbon black	PEL: 3.5 mg/m3	TLV: 3 mg/m3 (IHL)	No data.

Respiratory Equipment (Specify Type): Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Eye Protection: Safety glasses.

Protective Gloves: Wear appropriate gloves to prevent skin exposure.

Other Protective Clothing: Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation etc.): Use adequate ventilation to keep airborne concentrations low. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Work/Hygienic/Maintenance Practices: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: Appearance: Gray. Paste.
Odor: weak odor.

pH: No data.

Melting Point: No data.

Boiling Point: No data.

Flash Pt:	> 93.00 C
Evaporation Rate:	No data.
Flammability (solid, gas):	No data available.
Explosive Limits:	LEL: No data. UEL: No data.
Vapor Pressure (vs. Air or mm Hg):	No data.
Vapor Density (vs. Air = 1):	No data.
Specific Gravity (Water = 1):	~1.4
Solubility in Water:	No data.
Saturated Vapor Concentration:	No data.
Octanol/Water Partition Coefficient:	No data.
Autoignition Pt:	No data.
Decomposition Temperature:	No data.
Viscosity:	No data.

Information with regard to primary physical hazard:

10. Stability and Reactivity

Stability:	Unstable [X] Stable []
Conditions To Avoid - Instability:	Product will cure at ambient temperatures. Keep in cold storage until ready to use.
Incompatibility - Materials To Avoid:	Strong oxidizing agents, Strong acids.
Hazardous Decomposition or Byproducts:	Carbon oxides, nitrogen oxides (NOx).
Possibility of Hazardous Reactions:	Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions:	No data available.

11. Toxicological Information

Toxicological Information: No data available.
Irritation or Corrosion: Skin corrosion/irritation. Serious eye damage/irritation.
Sensitization: Skin sensitization.

12. Ecological Information

General Ecological Information: Toxic to aquatic life.

13. Disposal Considerations

Waste Disposal Method: Observe all federal, state, and local environmental regulations.

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: AMINES, SOLID, CORROSIVE, N.O.S. (Tetraethylene pentamine, Substituted piperazine)
DOT Hazard Class: 8 CORROSIVE
UN/NA Number: UN3259 **Packing Group:** III



MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: AMINES, SOLID, CORROSIVE, N.O.S. (Tetraethylene pentamine, Substituted piperazine)
UN Number: UN3259 **Packing Group:** III
Hazard Class: 8 - CORROSIVE
IMDG MFAG Number:
Marine Pollutant: Yes

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: AMINES, SOLID, CORROSIVE, N.O.S. (Tetraethylene pentamine, Substituted piperazine)
UN Number: UN3259 **Packing Group:** III
Hazard Class: 8 - CORROSIVE

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
7429-90-5	Aluminum	No	No	Yes
28768-32-3	4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline]	No	No	No
25068-38-6	Bisphenol-a based epoxy resin	No	No	No
112-57-2	Tetraethylenepentamine	No	No	No
7209-38-3	1,4-Bis(3-aminopropyl)piperazine	No	No	No
NA	Modified Epoxy Resin	No	No	No
112945-52-5	Silica, amorphous treated	No	No	No
4067-16-7	3,6,9,12-Tetraazatetradecamethylenediamine	No	No	No
65997-17-3	Fibrous glass	No	No	No

112-24-3	1,2-Ethanediamine, N,N'-Bis(2-aminoethyl)-	No	No	No
1333-86-4	Carbon black	No	No	No

California Proposition 65



WARNING

This product can expose you to chemicals including Carbon black, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
7429-90-5	Aluminum	TSCA: Inventory
28768-32-3	4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline]	TSCA: Inventory
25068-38-6	Bisphenol-a based epoxy resin	TSCA: Inventory
112-57-2	Tetraethylenepentamine	TSCA: Inventory
7209-38-3	1,4-Bis(3-aminopropyl)piperazine	TSCA: Inventory
NA	Modified Epoxy Resin	TSCA: Inventory
112945-52-5	Silica, amorphous treated	TSCA: Inventory
4067-16-7	3,6,9,12-Tetraazatetradecamethylenediamine	TSCA: Inventory
65997-17-3	Fibrous glass	TSCA: Inventory
112-24-3	1,2-Ethanediamine, N,N'-Bis(2-aminoethyl)-	TSCA: Inventory
1333-86-4	Carbon black	TSCA: Inventory CA PROP.65: Yes: Canc.

Regulatory Information: California Proposition 65: This product contains a chemical known in the state of California to cause cancer.

16. Other Information

Revision Date: 07/12/2023

Additional Information About This Product: No data available.

Company Policy or Disclaimer: The information on this data sheet represents our current and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or the applicable technical bulletin, or which involves using the product in combination with any other product or any other process is the responsibility of the user.