

Page: 1 of 6

Revision: 12/22/2023 Supersedes Revision: 12/17/2018

1. Product and Company Identification

Product Code: 3035 **Product Name:** 3035

Appli-Tec, Inc **Phone Number: Company Name:** (603)685-0500

7 Industrial Way Unit 1 Salem, NH 03079

Web site address: www.appli-tec.com

Emergency Contact: Contact medical emergency services

Call Chemtrec for Transport Info. Information: (800)424-9300

Intended Use: Adhesive

2. Hazards Identification

Combustible Dust

Acute Toxicity: Inhalation, Category 4 Skin Corrosion/Irritation, Category 1B

Serious Eye Damage/Eye Irritation, Category 1

Skin Sensitization, Category 1 Carcinogenicity, Category 2

Specific Target Organ Toxicity (repeated exposure), Category 1

Aquatic Toxicity (Chronic), Category 2









GHS Signal Word: Danger

GHS Hazard Phrases: H312 - Harmful in contact with skin.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H332 - Harmful if inhaled.

H351 - Suspected of causing cancer.

H372 - Causes damage to organs through prolonged or repeated exposure.

H411 - Toxic to aquatic life with long lasting effects.

GHS Precautionary

P201 - Obtain special instructions before use.

Phrases: P202 - Do not handle until all safety precautions have been read and

understood.

P260 - Do not breathe vapors, mist or spray. P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/eye protection/face protection.

P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. **GHS Response Phrases:**

P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all

contaminated clothing. Rinse skin with water/shower.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

GHS format Licensed to Appli-Tec



Page: 2 of 6

Revision: 12/22/2023 Supersedes Revision: 12/17/2018

P308+313 - IF exposed or concerned: Get medical attention/advice.

P314 - Get medical attention/advice if you feel unwell.

P333+313 - If skin irritation or rash occurs, seek medical advice/attention.

P363 - Wash contaminated clothing before reuse.

P391 - Collect spillage.

GHS Storage and Disposal P405 - Store locked up. P501 - Dispose of contents/container according to

Phrases: national and local regulations.

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

Inhalation: Harmful if inhaled. May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Skin Contact: Causes skin burns. May cause allergic skin reaction. **Eye Contact:** Causes eye burns. Causes serious eye damage.

Ingestion:Fatal if swallowed.Additional InformationNo data available.

3. Composition/Information on Ingredients

CAS#	Hazardous Components (Chemical Name)	Concentration
7440-02-0	Nickel	50.0 -85.0 %
25068-38-6	Bisphenol-a based epoxy resin	8.0 -35.0 %
111-40-0	Diethylenetriamine	1.0 -5.0 %
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	1.0 -5.0 %
98-00-0	Furfuryl alcohol	0.1 -5.0 %
9003-36-5	Phenol, polymer with (chloromethyl)oxirane and formaldehyde	0.1 -5.0 %
2425-79-8	1,4-Butanedioldiglycidyl ether	0.1 -1.0 %
56-81-5	Glycerin	0.1 -1.0 %
140-31-8	1-(2-Aminoethyl)piperazine	0.0 -0.1 %

Additional Information Exact percentages have been withheld as a trade secret.

4. First Aid Measures

Emergency and First Aid

Procedures:

In Case of Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get immediate medical attention.

In Case of Skin Contact: Remove contaminated clothing. Wash skin with soap and water. Get medical

attention. Wash contaminated clothing before reuse.

In Case of Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally

lifting the upper and lower eyelids. Get medical attention/advice.

In Case of Ingestion: Do NOT induce vomiting. Never give anything by mouth to an unconscious

person. Get medical advice/attention.

Licensed to Appli-Tec GHS format



Page: 3 of 6

Revision: 12/22/2023 Supersedes Revision: 12/17/2018

5. Fire Fighting Measures

Flash Pt: > 93.00 C

LEL: No data. **Explosive Limits:** UEL: No data.

Autoignition Pt: No data.

Suitable Extinguishing

Use water spray, dry chemical, carbon dioxide, or appropriate foam.

Media:

Fire Fighting Instructions: As in any fire, wear a self-contained breathing apparatus in pressure-demand.

MSHA/NIOSH (approved or equivalent), and full protective gear.

Flammable Properties and No data available.

Hazards:

No data available. **Hazardous Combustion**

Products:

6. Accidental Release Measures

Material Is Released Or

Spilled:

Steps To Be Taken In Case Ensure adequate ventilation. Isolate area and deny entry. Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Use proper personal protective equipment as indicated in Section 8. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

7. Handling and Storage

Precautions To Be Taken

in Handling:

Use with adequate ventilation. Avoid ingestion and inhalation. Avoid contact with

eyes, skin, and clothing. Normal measures for preventive fire protection.

Precautions To Be Taken

Store at <= -40deg.C.

in Storing:

8. Exposure Controls/Personal Protection							
CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits			
7440-02-0	Nickel	PEL: 1 mg/m3	TLV: 1.5 mg/m3 (Inhalation)	No data.			
25068-38-6	Bisphenol-a based epoxy resin	No data.	No data.	No data.			
111-40-0	Diethylenetriamine	No data.	TLV: 1 ppm	No data.			
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamin e)	No data.	No data.	No data.			
98-00-0	Furfuryl alcohol	PEL: 50 ppm	TLV: 10 ppm STEL: 15 ppm	No data.			
9003-36-5	Phenol, polymer with (chloromethyl)oxirane and formaldehyde	No data.	No data.	No data.			
2425-79-8	1,4-Butanedioldiglycidyl ether	No data.	No data.	No data.			
56-81-5	Glycerin	PEL: 15 (dust); 5 (resp.) mg/m3	TLV: 10 mg/m3	No data.			
140-31-8	1-(2-Aminoethyl)piperazine	No data.	No data.	No data.			

Licensed to Appli-Tec **GHS** format



Page: 4 of 6

Revision: 12/22/2023 Supersedes Revision: 12/17/2018

Respiratory Equipment

(Specify Type):

Use a NIOSH/MSHA or European Standard EN 149 approved respirator if

exposure limits are exceeded or if irritation or other symptoms are experienced.

Eye Protection: Safety glasses.

Protective Gloves: Wear appropriate protective gloves to prevent skin exposure. Other Protective Clothing: Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation etc.):

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use process enclosure, local exhaust ventilation, or

other engineering controls to control airborne levels below recommended

exposure limits.

Work/Hygienic/Maintenanc Handle in accordance with good industrial hygiene and safety practice. Wash

hands before breaks and at the end of workday. e Practices:

9. Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid

Appearance: Gray. Paste. **Appearance and Odor:**

Odor: weak odor.

No data. pH: No data. **Melting Point: Boiling Point:** No data. Flash Pt: > 93.00 C No data. **Evaporation Rate:**

Flammability (solid,

No data available.

gas):

LEL: No data. UEL: No data. **Explosive Limits:**

Vapor Pressure (vs. Air

or mm Hg):

No data.

Vapor Density (vs. Air =

No data.

1):

Specific Gravity (Water =

~3.0

1):

Solubility in Water: No data. No data. **Saturated Vapor**

Concentration:

Octanol/Water Partition

No data.

Coefficient:

No data. **Autoignition Pt: Decomposition** No data.

Temperature:

Viscosity: No data.

Information with regard to primary physical

hazard:



Page: 5 of 6

Revision: 12/22/2023 Supersedes Revision: 12/17/2018

10. Stability and Reactivity

Stability: Unstable [X] Stable []

Conditions To Avoid -Product will cure at ambient temperatures. Keep in cold storage until ready to

Instability:

use.

Incompatibility - Materials Strong oxidizing agents.

To Avoid:

Hazardous Decomposition Carbon oxides, Nitrogen oxides, Ammonia.

or Byproducts:

Possibility of Hazardous Will occur [] Will not occur [X]

Reactions:

Conditions To Avoid -No data available.

Hazardous Reactions:

11. Toxicological Information

Toxicological Information: No data available.

Irritation or Corrosion: Serious eye damage/irritation. Skin corrosion/irritation.

Respiratory and skin sensitization. Sensitization:

12. Ecological Information

No data available.

13. Disposal Considerations

Observe all federal, state, and local environmental regulations. **Waste Disposal Method:**

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Amines, liquid, corrosive, n.o.s. (Diethylenetriamine,

4,7,10-Trioxatridecane-1-13-diamine) Name:

CORROSIVE DOT Hazard Class: 8

UN/NA Number: UN2735 **Packing Group:** Ш



MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Amines, liquid, corrosive, n.o.s. (Diethylenetriamine,

4,7,10-Trioxatridecane-1-13-diamine)

UN Number: UN2735 **Packing Group:** Ш

Hazard Class: 8 - CORROSIVE

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Amines, liquid, corrosive, n.o.s. (Diethylenetriamine,

4,7,10-Trioxatridecane-1-13-diamine)

Packing Group: UN Number: UN2735 Ш

8 - CORROSIVE **Hazard Class:**



Page: 6 of 6

Revision: 12/22/2023 Supersedes Revision: 12/17/2018

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists						
CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)		
7440-02-0	Nickel	No	Yes NA	Yes		
25068-38-6	Bisphenol-a based epoxy resin	No	No	No		
111-40-0	Diethylenetriamine	No	No	No		
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	No	No	No		
98-00-0	Furfuryl alcohol	No	No	No		
9003-36-5	Phenol, polymer with (chloromethyl)oxirane and formaldehyde	No	No	No		
2425-79-8	1,4-Butanedioldiglycidyl ether	No	No	No		
56-81-5	Glycerin	No	No	No		
140-31-8	1-(2-Aminoethyl)piperazine	No	No	No		

California Proposition 65



This product can expose you to chemicals including Nickel and Furfuryl alcohol, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

CAS#	Hazardous Components (Chemical Name)	Other US EPA or State Lists
7440-02-0	Nickel	TSCA: Inventory
		CA PROP.65: Yes: Canc.
25068-38-6	Bisphenol-a based epoxy resin	TSCA: Inventory
111-40-0	Diethylenetriamine	TSCA: Inventory
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	TSCA: Inventory
98-00-0	Furfuryl alcohol	TSCA: Inventory
		CA PROP.65: Yes: Canc.
9003-36-5	Phenol, polymer with (chloromethyl)oxirane and	TSCA: Inventory
	formaldehyde	
2425-79-8	1,4-Butanedioldiglycidyl ether	TSCA: Inventory, 8A
56-81-5	Glycerin	TSCA: Inventory
140-31-8	1-(2-Aminoethyl)piperazine	TSCA: Inventory

16. Other Information

Revision Date: 12/22/2023 Previous revision: 12/17/2018

Additional Information About This Product:

Company Policy or Disclaimer:

No data available.

The information on this data sheet represents our current and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or the applicable technical bulletin, or which involves using the product in combination with any other product or any other process is the responsibility of the user.

Licensed to Appli-Tec GHS format